Safety Data Sheet



1. Identification

Product Information: 21900915

Family: 509

Product Name: ADVANCED e-CLEAR 4.1

Recommended Use: Pintura / Recubrimiento

SUR QUIMICA S.A.

Supplied by/Manufacturer: Calle 38, contiguo al Cementerio La Uruca.

San José, Costa Rica, Centroamérica Tel Información: (506) 2211-3700,

Fax: (506) 2256-0690

Emergency Telephone: CHEMTREC: 1-800-424-9300 (USA)

703-527-3887

Safety Data Sheet Coordinator: sds@gruposur.com

2. Hazards Identification

GHS Classification

Acute Tox. 3 Inhalation, Eye Dam. 1, Flam. Liq. 3, Repr. 1A, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 NE, STOT SE 3 RTI

Symbol(s) of Product









Signal Word

Danger

Possible Hazards

17.3% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 3 H226 Flammable liquid and vapour.

Skin Irritation, category 2 H315 Causes skin irritation.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.
Serious Eye Damage, category 1 H318 Causes serious eye damage.

Acute Toxicity, Inhalation, category 3 H331 Toxic if inhaled.

STOT, single exposure, category 3, RTI H335 May cause respiratory irritation.

STOT, single exposure, category 3, NE H336 May cause drowsiness or dizziness.

Reproductive Toxicity, category 1A H360 May damage fertility or the unborn child.

STOT, repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P310 Immediately call a POISON CENTER or doctor/physician.

P311 Call a POISON CENTER or doctor/physician.
P321 Specific treatment (see FIRST AIDS on this sheet).
P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use materials indicated in Section 5 to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
n-Butyl Acetate	123-86-4	30-40	GHS02-GHS06	H225-315-320-331-336
1-methyl-2-methoxiethyl acetate	108-65-6	10-20	GHS02-GHS05-	H226-315-318-335-360
			GHS07-GHS08	
Xilene	1330-20-7	2.5-10	GHS02-GHS07	H225-304-312-315-319-332-335
			-GHS08	-373
Isobutyl methyl ketone	108-10-1	2.5-10	GHS02-GHS07	H225-319-332-335
Petroleum Hidrocarbon	64742-95-6	2.5-10	GHS02-GHS07-	H226-304-317-335-336
			GHS08	

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: Artificial respiration and/or oxygen may be necessary. Keep the victim calm. Ensure that medical personnel are aware of the materials involved and take precautions to protect themselves. Oxygen or artificial respiration if needed.

If inhaled, remove to fresh air. Give oxygen if necessary. Consult a physician if symptoms persist or exposure is severe.

FIRST AID - SKIN CONTACT: Seek medical advice. In case of skin contact, wash immediately with plenty of water for at least 20 minutes. In case of contact, wash skin immediately with soap and water. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. In case of burns, immediately wash skin with cold water. Seek medical advice. Do not remove clothes stick to the skin. Seek medical advice.

FIRST AID - EYE CONTACT: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

FIRST AID - INGESTION: If ingested, do not induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heating may cause an explosion. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). When heated, emits highly irritating and noxious vapors.

SPECIAL FIREFIGHTING PROCEDURES: Do not use a solid water stream as it may scatter and spread fire. Move containers from fire area if you can do it without risk. All these products have a very low flash point: Use of water spray when fighting fire may be inefficient. Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: Do not allow to enter drains, sewers, or sewers.

Inform the authorities in the event of a leak in natural water courses or in the sewage system.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Water spray can reduce vapours, but may not prevent ignition in enclosed spaces. Ventilate closed spaces before entering. All equipment used when handling the product must be grounded. Use clean, non-sparking tools to collect absorbed material. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent entry into waterwatys, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift. Absorb or cover with dry earth, sand or other non-combustible material and trasfer to containers. Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

7. Handling and Storage





HANDLING: Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Keep out of reach of children. Take precautionary measures against static discharges. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning.

STORAGE: Keep in a dry, cool and well-ventilated place. Once used, the container should be closed and keep in a well ventilated area and in vertical position to prevent losses. Keep containers closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
n-Butyl Acetate	150 ppm	N.E.	N.E.	N.E.
1-methyl-2-methoxiethyl acetate	50 mg/L	100 mg/L	N.E.	N.E.
Xilene	20 ppm 8h	150 ppm 15 min	100 ppm 8h	N.E.
Isobutyl methyl ketone	20 ppm	75 ppm	N.E.	N.E.
Petroleum Hidrocarbon	25	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In case of insufficient ventilation, wear suitable respiratory equipment.



SKIN PROTECTION: Wear nitrile or neoprene gloves. Gloves should be inspectet before use. Use the correct technique to remove the gloves (without touching the exterior surface) to prevent skin contact with the product.



EYE PROTECTION: Wear chemical goggles and faceshield (if not wearing a full facepiece respirator). Wear approved eye protection according to applicable governmental regulations.



OTHER PROTECTIVE EQUIPMENT: When required, according to the concentration of the product, wear chemical protective clothing with limited thermal protection.



HYGIENIC PRACTICES: Wash hands and face before breaks and immediately after handling the product. Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

9. Physical and Chemical Properties

Appearance: Líquido Physical State: Líquido

Odor: Característico Odor Threshold, ppb: No Information

Density, g/ml: 0.957 **pH:** N.A.

Freeze Point, °C: No Information Viscosity, cP: No Information Solubility in Water: No Partition Coefficient, n-octanol/ No Information

Decomposition temperature, °C No Information water:

Boiling Range, °C: 79 - 350 **Explosive Limits, %:** 0.0 - 12.0

Combustibility: Does not Support Combustion Flash Point, °C: 31

Evaporation Rate: No Information Auto-Ignition Temperature, °C No Information Vapor Density: No Information Vapor Pressure, mmHg: No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Keep away from sources of ignition: heat, flame and sparks.

INCOMPATIBILITY: Oxidizing agents, strong acids and strong bases. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological Information



Practical Experiences

INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity: No Information

Skin corrosion/irritation: No Information

Serious eye damage/eye irritation: No Information Respiratory or skin sensitisation: No Information

Germ cell mutagenicity: No Information

Carcinogenicity: No Information

Reproductive toxicity: No Information

Specific target organ toxicity - single exposure: No Information

Specific target organ toxicity - repeated exposure: No Information

Aspiration hazard: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50 (mg/kg)	Vapor LC50
123-86-4	n-Butyl Acetate	7400	N.I.	2000
108-65-6	1-methyl-2-methoxiethyl acetate	8532	>2000	10000
1330-20-7	Xilene	4300	N.I.	N.I.
108-10-1	Isobutyl methyl ketone	2080	5990	16.4

N.I. = No Information

Product's Dermal Toxicity: 4,911.14 mg/kg

12. Ecological Information

Toxicity: No Information

Persistence and Degradability: No Information

Bioaccumulative potential: No Information

Mobility in the soil: No Information

Other adverse effects: No Information

13. Disposal Information

DISPOSAL METHOD: Prevent entry into waterways, sewers, basements or confined areas.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Sea Transport

UN Number: 1263

IMDG/GGVSee Class: No Information

Packing Group:

Shipping Name: Pintura o Material Relacionado a Pintura

Marine Pollutant:

Shipping Hazard(Marine Pollutant):

No Information

No Information

Air Transport

UN Number: 1263

ICAO/IATA Class: No Information

Packing Group:

Shipping Name: Pintura o Material Relacionado a

_....

15. Regulatory Information

No information available

16. Other Information

Revision Date: 02-10-2017 Supersedes Date: New MSDS

Reason for revision: No Information

Datasheet produced by: SUR Química S.A.

Hazardous Material Information System: HMIS

Health	2	Flammability	3	Reactivity	0	Personal Protection	G	Chronic Hazard	No	Target Organ	N/A	
--------	---	--------------	---	------------	---	------------------------	---	-------------------	----	-----------------	-----	--

National Fire Protection Association: NFPA

Flammability	3	Health	2	Reactivity	0	Special Hazards	N/A	
								1

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H319 Causes serious eye irritation.
H320 Causes eye irritation
H331 Toxic if inhaled.

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H360 May damage fertility or the unborn child.

Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02

H332





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

No Information