Safety Data Sheet



1. Identification

Product Information: 00407100

Family: 511

Product Name: TRAFFIC PAINT 407 YELLOW

Recommended Use: Painting / Coating

SUR QUIMICA S.A.

Supplied by/Manufacturer: Calle 38, contiguo al Cementerio La Uruca.

San José, Costa Rica, Centroamérica Tel Información: (506) 2211-3700,

Fax: (506) 2256-0690

Emergency Telephone: CHEMTREC: 1-800-424-9300INTERNATIONAL: (506)

2211-3911

Safety Data Sheet Coordinator: sds@gruposur.com

2. Hazards Identification

GHS Classification

Aquatic Chronic 2, Carc. 1A, Eye Irrit. 2A, Flam. Lig. 2, Repr. 1A, Skin Irrit. 2, Skin Sens. 1, STOT SE 2

Symbol(s) of Product









Signal Word Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 2 H225 Highly flammable liquid and vapour. Skin Irritation, category 2 H315 Causes skin irritation.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction. Eye Irritation, category 2A H319 Causes serious eye irritation.

Carcinogenicity, category 1A H350 May cause cancer.

Reproductive Toxicity, category 1A H360 May damage fertility or the unborn child.

STOT, single exposure, category 2 H371 May cause damage to organs.

Hazardous to the aquatic environment, H411 Toxic to aquatic life with long lasting effects.

Chronic, category 2

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor/...
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see FIRST AIDS on this sheet).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use materials indicated in Section 5 to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Remove the contents / container according to the General Regulation for the

Classification and Management of Hazardous Waste No. 41527-S-MINAE (Applies to Costa Rica). Dispose of contents/container in accordance with local/regional/national/

international regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P270 Do not eat, drink or smoke when using this product.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
Toluene	108-88-3	10-20	GHS02-GHS07- GHS08	H225-304-315-319-332-336-3 61-371
Pigment Lead Chromate	1344-37-2	2.5-10	GHS08-GHS09	H350-360-373-410
Xilene	1330-20-7	2.5-10	GHS07	H303-313-315
Alkyl Quaternary Ammonium Bentonite	68953-58-2	0.1-1.0	No Information	No Information
Methylethyl ketoxime	96-29-7	0.1-1.0	GHS05-GHS07- GHS08	H302-313-317-318-351
2-Ethylhexanoic acid	149-57-5	<0.1	GHS07 -GHS08	H303-312-361

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: Artificial respiration and/or oxygen may be necessary. Keep the victim calm. Ensure that medical personnel are aware of the materials involved and take precautions to protect themselves. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. Give oxygen if necessary. Consult a physician if symptoms persist or exposure is severe.

FIRST AID - SKIN CONTACT: Seek medical advice. In case of skin contact, wash immediately with plenty of water for at least 20 minutes. In case of contact, wash skin immediately with soap and water. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. In case of burns, immediately wash skin with cold water. Seek medical advice. Do not remove clothes stick to the skin. Seek medical advice.

FIRST AID - EYE CONTACT: Flush eye(s) immediately with plenty of water. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

FIRST AID - INGESTION: If ingested, do not induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Burns with colorless flame. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard. This material increases the risk of fire and may aid combustion. Heating may cause a fire. May re-ignite itself after fire is extinguished. Hazardous decomposition may occur.

SPECIAL FIREFIGHTING PROCEDURES: Do not use a solid water stream as it may scatter and spread fire. Move containers from fire area if you can do it without risk. All these products have a very low flash point: Use of water spray when fighting fire may be inefficient. Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: Inform the authorities in the event of a leak in natural water courses or in the sewage system.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Water spray can reduce vapours, but may not prevent ignition in enclosed spaces. Ventilate closed spaces before entering. All equipment used when handling the product must be grounded. Use clean, non-sparking tools to collect absorbed material. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent entry into waterwatys, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift. Absorb or cover with dry earth, sand or other non-combustible material and trasfer to containers. Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

7. Handling and Storage





HANDLING: Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Keep out of reach of children. Take precautionary measures against static discharges. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning.

STORAGE: Keep in a dry, cool and well-ventilated place. Once used, the container should be closed and keep in a well ventilated area and in vertical position to prevent losses.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Toluene	20 ppm	N.E.	200 ppm	N.E.
Pigment Lead Chromate	0.05 mg/m3	N.E.	N.E.	N.E.
Xilene	20 ppm 8h	150 ppm 15 min	100 ppm 8h	N.E.
Alkyl Quaternary Ammonium Bentonite	N.E.	N.E.	N.E.	N.E.
Methylethyl ketoxime	N.E.	N.E.	N.E.	N.E.
2-Ethylhexanoic acid	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In case of insufficient ventilation, wear suitable respiratory equipment.



SKIN PROTECTION: Do not wear leather gloves. Wear nitrile or neoprene gloves. Gloves should be inspectet before use. Use the correct technique to remove the gloves (without touching the exterior surface) to prevent skin contact with the product.



EYE PROTECTION: Wear chemical goggles and faceshield (if not wearing a full facepiece respirator). Wear approved eye protection according to applicable governmental regulations.



OTHER PROTECTIVE EQUIPMENT: When required, according to the concentration of the product, wear chemical protective clothing with limited thermal protection.



HYGIENIC PRACTICES: Wash hands and face before breaks and immediately after handling the product. Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

water:

9. Physical and Chemical Properties

Appearance: Liquid Physical State: Liquid

Odor: Characteristic Odor Threshold, ppb: No Information

Density, g/ml: 1.548 **pH:** N.A.

Freeze Point, °C: No Information Viscosity, cP: No Information Solubility in Water: No Partition Coefficient, n-octanol/ No Information

Solubility in Water: No

Decomposition temperature, °C No Information

process of process, and monitoring

Boiling Range, °C: 80 - 80 Explosive Limits, %: 0.0 - 99.0

Combustibility: Sin Información Flash Point, °C: 19

Evaporation Rate:No InformationAuto-Ignition Temperature, °CNo InformationVapor Density:No InformationVapor Pressure, mmHg:No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Keep away from sources of ignition: heat, flame and sparks.

INCOMPATIBILITY: Oxidizing agents, strong acids and strong bases. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological Information



Practical Experiences

INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity: Contains lead-derived compounds: Direct exposure of solid particles of lead can have cardiovascular involvement (blood vessels and heart), can cause weakness in the fingers, wrists or ankles. Exposure to lead also produces a small increase in blood pressure, especially in middle-aged and elderly people and can cause anemia. Exposure to high levels of lead can seriously damage the brain and kidneys of children and adults and cause death.

Skin corrosion/irritation: t causes severe burns on the skin. Direct dermal contact for a prolonged period can cause skin damage because it removes the lipids present, causing dryness, cracking and dermatitis; to these effects a break and fall of the exposed skin can follow.

Serious eye damage/eye irritation: Causes serious eye injuries. Severely irritating to the eyes. It can cause severe burns to eyes and skin. Adverse symptoms may include pain, tearing and redness.

Respiratory or skin sensitisation: No Information

Germ cell mutagenicity: No Information

Carcinogenicity: Contains lead derivatives: Inorganic compounds containing lead are categorized by IARC into group 2A likely to be carcinogenic in humans.

Reproductive toxicity: contains lead derivatives: direct exposure to lead particles can cause alterations in the development of the fetus (effects during periods in which organs develop), in the gastrointestinal system (digestive), hematological system (blood formation), skeletal muscle (muscles and skeleton), neurological (nervous system), ocular (eyes), renal (Urinary system or kidneys) and reproductive (producing children). Exposure to high levels of lead can lead to pregnancy loss. In men, exposure to high levels can alter sperm production

Specific target organ toxicity - single exposure: No Information

Specific target organ toxicity - repeated exposure: Contains lead chromate, prolonged exposure of adults can cause a general deterioration of health, negatively affects the nervous system in the result of some tests that measure basic functions.

Aspiration hazard: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50 (mg/kg)	Vapor LC50
108-88-3	Toluene	5580	12196	20
1344-37-2	Pigment Lead Chromate	>5000	>5000	>20
1330-20-7	Xilene	4300	>4200	30
96-29-7	Methylethyl ketoxime	930	2702	N.I.
149-57-5	2-Ethylhexanoic acid	3000	2000	>20

N.I. = No Information

Toxicidad Dermal del producto: 84,447.15 mg/kg

12. Ecological Information

Toxicity: No Information

Persistence and Degradability: No Information Bioaccumulative potential: No Information

Mobility in the soil: No Information

Other adverse effects: No Information

13. Disposal Information

DISPOSAL METHOD: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Prevent entry into waterways, sewers, basements or confined areas.

Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Sea Transport

UN Number: 1263
IMDG/GGVSee Class: 3
Packing Group: II

Shipping Name: Pintura o Material Relacionado con Pintura

Marine Pollutant: No

Shipping Hazard(Marine Pollutant): No Information

Air Transport

UN Number: 1263
ICAO/IATA Class: 3
Packing Group: II

Shipping Name: Pintura o Material Relacionado con Pintura

15. Regulatory Information

No information available

16. Other Information

Revision Date: 27/11/2024 **Supersedes Date:** 27/11/2024

Reason for revision: Product Composition Changed

Substance Hazardous Flag Changed

Substance and/or Product Properties Changed in Section(s):

03 - Composition/Information on Ingredients

09 - Physical & Chemical Information

Datasheet produced by: SUR Química S.A.

Hazardous Material Information System: HMIS

Health	2	Flammability	3	Reactivity	0	Personal Protection	G	Chronic Hazard	Sí	Target Organ	RIÑON ES	
--------	---	--------------	---	------------	---	------------------------	---	-------------------	----	-----------------	-------------	--

National Fire Protection Association: NFPA

Flammability	3	Health	2	Reactivity	0	Special Hazards	N/A	
								1

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour. Harmful if swallowed. H302 H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. May be harmful in contact with skin. H313 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. Causes serious eye irritation. H319 H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H350 May cause cancer. Suspected of causing cancer. H351 H360 May damage fertility or the unborn child. H361 Suspected of damaging fertility or the unborn child. May cause damage to organs. H371 H373 May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02
GHS05

H410



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

No Information