Safety Data Sheet



1. Identification					
Product Information:	11770905				
Family:	518				
Product Name:	ACABADO SATINADO PARA EXTERIORES TRANSPARENTE				
Recommended Use:	Painting / Coating				
Supplied by/Manufacturer:	SUR QUIMICA S.A. Calle 38, contiguo al Cementerio La Uruca. San José, Costa Rica, Centroamérica Tel Información: (506) 2211-3700, Fax: (506) 2256-0690				
Emergency Telephone:	CHEMTREC: 1-800-424-9300 INTERNATIONAL: (506) 2211-3911				
Safety Data Sheet Coordinator:	sds@gruposur.com				

2. Hazards Identification

GHS Classification

Aquatic Acute 3, Aquatic Chronic 3, Flam. Liq. 3, Skin Irrit. 2

Symbol(s) of Product



Signal Word Warning

GHS HAZARD STATEMENTS Flammable Liquid, category 3

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Hazardous to the aquatic environment, Acute, category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
GHS LABEL PRECAUTIONARY STATEMENTS		
P210	Keep away smoking.	from heat, hot surfaces, sparks, open flames and other ignition sources. No
P233	Keep contai	ner tightly closed.
P264	Wash skin t	horoughly after handling.
P273	Avoid releas	se to the environment.
P280	Wear protect	tive gloves/protective clothing/eye protection/face protection.
P302+P352	•	: Wash with plenty of soap and water.

Date Printed: 4/8/2021

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
Specific treatment (see FIRST AIDS on this sheet).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use materials indicated in Section 5 to extinguish.
Collect spillage.
Store in a well-ventilated place. Keep cool.
Remove the contents / container according to the General Regulation for the Classification and Management of Hazardous Waste No. 41527-S-MINAE (Applies to Costa Rica).Dispose of contents/container in accordance with local/regional/national/ international regulations.
IENTS
Ground and bond container and receiving equipment.
Use explosion-proof [electrical/ventilating/lighting/] equipment.
Use non-sparking tools.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
Xilene	1330-20-7	30-40	GHS07	H303-313-315
1-methyl-2-methoxiethyl acetate	108-65-6	2.5-10	GHS02	H226-313
Isobutyl methyl ketone	108-10-1	2.5-10	GHS02-GHS07	H225-303-319-332-335
Toluene	108-88-3	0.1-1.0	GHS02-GHS07 -GHS08	H225-304-315-319-332-336-3 61-371
Dilaurato de dibutilestaño	77-58-7	0.1-1.0	GHS05-GHS07- GHS08-GHS09	H303-313-314-317-341-360-3 70-372-400-410

Take action to prevent static discharges.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



P243

FIRST AID - INHALATION: Artificial respiration and/or oxygen may be necessary. Keep the victim calm. Ensure that medical personnel are aware of the materials involved and take precautions to protect themselves. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. Give oxygen if necessary. Consult a physician if symptoms persist or exposure is severe.

FIRST AID - SKIN CONTACT: Seek medical advice. In case of skin contact, wash immediately with plenty of water for at least 20 minutes. In case of contact, wash skin immediately with soap and water. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. In case of burns, immediately wash skin with cold water. Seek medical advice. Do not remove clothes stick to the skin. Seek medical advice.

FIRST AID - EYE CONTACT: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

FIRST AID - INGESTION: If ingested, do not induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heating may cause an explosion. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). When heated, emits highly irritating and noxious vapors.

SPECIAL FIREFIGHTING PROCEDURES: Do not use a solid water stream as it may scatter and spread fire. Move containers from fire area if you can do it without risk. All these products have a very low flash point: Use of water spray when fighting fire may be inefficient. Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: Do not allow to enter drains, sewers, or sewers. Inform the authorities in the event of a leak in natural water courses or in the sewage system.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Water spray can reduce vapours, but may not prevent ignition in enclosed spaces. Ventilate closed spaces before entering. All equipment used when handling the product must be grounded. Use clean, non-sparking tools to collect absorbed material. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent entry into waterwatys, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift. Absorb or cover with dry earth, sand or other non-combustible material and trasfer to containers. Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

7. Handling and Storage



HANDLING: Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Never use air pressure for transferring product. Use only in well-ventilated areasHandle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Keep out of reach of children. Take precautionary measures against static discharges. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning.

STORAGE: Keep in a dry, cool and well-ventilated place. Once used, the container should be closed and keep in a well ventilated area and in vertical position to prevent losses. Keep containers closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits								
Chemical Name	<u>ACGIH TLV-TWA</u>	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING				
Xilene	20 ppm 8h	150 ppm 15 min	100 ppm 8h	N.E.				
1-methyl-2-methoxiethyl acetate	50 mg/L	100 mg/L	N.E.	N.E.				
Isobutyl methyl ketone	20 ppm	75 ppm	N.E.	N.E.				
Toluene	20 ppm	N.E.	200 ppm	N.E.				
Dilaurato de dibutilestaño	N.E.	N.E.	N.E.	N.E.				

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection

RESPIRATORY PROTECTION: In case of insufficient ventilation, wear suitable respiratory equipment.



SKIN PROTECTION: Wear nitrile or neoprene gloves. Gloves should be inspectet before use. Use the correct technique to remove the gloves (without touching the exterior surface) to prevent skin contact with the product.



EYE PROTECTION: Wear chemical goggles and faceshield (if not wearing a full facepiece respirator). Wear approved eye protection according to applicable governmental regulations.



OTHER PROTECTIVE EQUIPMENT: When required, according to the concentration of the product, wear chemical protective clothing with limited thermal protection.



HYGIENIC PRACTICES: 022 <undefined>Wash hands and face before breaks and immediately after handling the product. Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Characteristic	Odor Threshold, ppb:	Not Established
Density, g/ml:	0.997	pH:	N.A.
Freeze Point, °C:	No Information	Viscosity, cP:	
Solubility in Water:	No	Partition Coefficient, n-octanol/	No Information
Decomposition temperature, °C	No Information	water:	
Boiling Range, °C:	0 - 0	Explosive Limits, %:	120.0 - 99.0
Combustibility:	Sin Información	Flash Point, °C:	28
Evaporation Rate:		Auto-Ignition Temperature, °C	No Information
Vapor Density:	No Information	Vapor Pressure, mmHg:	No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Keep away from sources of ignition: heat, flame and sparks.

INCOMPATIBILITY: Oxidizing agents, strong acids and strong bases. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological Information



Practical Experiences

INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity: No Information Skin corrosion/irritation: No Information Serious eye damage/eye irritation: No Information Respiratory or skin sensitisation: No Information Germ cell mutagenicity: No Information Carcinogenicity: No Information Reproductive toxicity: No Information Specific target organ toxicity - single exposure: No Information Specific target organ toxicity - repeated exposure: No Information Aspiration hazard: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	<u>Oral LD50</u>	<u>Dermal LD50 (mg/</u> <u>kg)</u>	Vapor LC50
1330-20-7	Xilene	4300	>4200	30
108-65-6	1-methyl-2-methoxiethyl acetate	8532	>2000	>20
108-10-1	Isobutyl methyl ketone	2080	5990	16.4
108-88-3	Toluene	5580	12196	20
77-58-7	Dilaurato de dibutilestaño	2071	>2000	>20

N.I. = No Information

Toxicidad Dermal del producto: 7,451.75 mg/kg

12. Ecological Information

Toxicity: No Information

Persistence and Degradability: No Information

Bioaccumulative potential: No Information

Mobility in the soil: No Information

Other adverse effects: No Information

13. Disposal Information

DISPOSAL METHOD: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Prevent entry into waterways, sewers, basements or confined areas.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Sea Transport	
UN Number:	1263
IMDG/GGVSee Class:	3
Packing Group:	Ш
Shipping Name:	Paint or material related to paint
Marine Pollutant:	No Information
Shipping Hazard(Marine Pollutant):	No Information
Air Transport	
UN Number:	1263
ICAO/IATA Class:	3
Packing Group:	Ш
Shipping Name:	Paint or material related to paint

15. Regulatory Information

No information available

16. Other Information Revision Date: 4/8/2021 Supersedes Date: New MSDS Reason for revision: No Information New MSDS

					-			_	
Hazardo	ous Mate	erial Informatior	n System	: HMIS					
Datashe	et produ	ced by: S	UR Quím	ica S.A.					
i lousoff i									

Health2Flammability3Reactivity0Personal
ProtectionGChronic
HazardNoTarget
OrganN/A


National Fire Protection Association: NFPA

Flamm	ability	3	Health	2	Reactivity	0	Special Hazards	N/A
-------	---------	---	--------	---	------------	---	-----------------	-----

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained in this safety sheet has been prepared for SUR QUIMICA S.A. based on the data provided by suppliers and manufacturers of the raw materials involved. This document is intended to be a guide for safe use according to use. The user receiving this information must be properly trained and be able to use his independent judgment to determine its applicability in particular uses. This safety data sheet (SDS) does not in any way exempt the user from knowing and complying with the good practices and rules of use applicable to their activity. The user must assume full responsibility to know and take precautions related to the use of the product. The exposure scenario is subject to revision and changes. The user must ensure that they have the latest version of the FDS. The updated versions are available on the website www.gruposur.com