

# TECHNICAL INFORMATION

## LINDSEED OIL ACEITE DE LINAZA

504-00361-900



### DESCRIPTION

Lindseed Oil was made from natural oils and resins, specially formulated for wood treatment. It can be applied over any wood, as long as it has never been painted or varnished, to enhance and protect its natural appearance.

### USE

Recommended to permeate Wood structures located indoors.

Structure	Any Wood structure
Exterior/Interior	Indoor
Surface	Wood
Product line	Domestic/Professional/Industrial Line

### CHARACTERISTICS

PHYSICAL PROPERTY	DATA
Volume Solids (%)	45 - 49
Weight solids (%)	51 - 55
Weight per Gallon (kg/Gl)	3.35 - 3.45
Viscosidad copa Ford # 4 (s)	30 - 40
Theoretical Yield (m <sup>2</sup> /Gallon)	70 - 72

Definition of theoretical yield: Maximum surface that a paint can cover under ideal conditions. Practical performance varies depending on type of surface, used tool, applicator experience and other factors. 1 mil = 0.0254 mm.

### PRESENTATION

#### AVAILABLE PRESENTATIONS

1 / 4 gl metal can (0.946 lt)

1 gl metal can (3.785 lt)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator' skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.

# TECHNICAL INFORMATION

## LINDSEED OIL ACEITE DE LINAZA

504-00361-900



### SURFACE PREPARATION

CONDITION	INSTRUCTION
<b>Painted or varnished Wood.</b>	Wood should NOT be painted or varnished, because wood's pores would be sealed and the product could not perform as desired.
<b>Wood's sanding:</b>	Wood must be sanded with # 100 -120 grit.
<b>Planed wood:</b>	Wood must be planed, sanded, free of dust, oils or any other contaminants.
<b>Moisture</b>	Wood must have a moisture content of 16% or less.

### PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 504-00361-900 - Lindseed Oil	<b>100%</b>	Ready to use. Do not dilute:

Stir the container until the product is completely homogenous.

### PRODUCT APPLICATION

#### IT CAN BE APPLIED WITH



Clean cloth or rag



Clean Cloth, Rag, Wick or tow.

#### Application conditions

Apply and, after a few minutes, wipe off excesses.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator's skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.

# TECHNICAL INFORMATION

## LINDSEED OIL ACEITE DE LINAZA



504-00361-900

### Number of layers and thickness

Number of Coats	1 or 2 as required
-----------------	--------------------

### Drying times

Recoat time	12 h
-------------	------

Total drying time	72 h
-------------------	------

Drying times listed are under ideal conditions (Between 22-28°C temperature and 50 - 80% relative humidity). These times are dependent on temperature, moisture, film thickness and dilution.

### Maintenance

To clean finished surfaces, use our CAREWOOD CONDITIONER 518-38901-900.

### OBSERVATIONS

- ✓ If you need more information, one of our technicians will assist you.  
Call 800-SUR-2000 or email us at [customerservice@gruposur.com](mailto:customerservice@gruposur.com)
- ✓ Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Wood pieces finished with this oil should not be in contact with food.

### HEALTH

- ✓ User may need to wear appropriate personal protective equipment, as detailed in the respective safety data sheet (MSDS), available at [www.gruposur.com](http://www.gruposur.com)
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator' skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.