

PEGA ALL

505-00230-000

DESCRIPTION

Single-part acrylic adhesive putty used in the construction industry, designed to glue decorative tiles on low-absorption surfaces. It can be used to glue tiles, tiles, trim moldings or any other decorative element on concrete, wood, metal, fiber cement, bricks or other similar. Also suitable for laying polystyrene trim moldings or used as an elastomeric mortar to fill or leveling cementitious surfaces, in thinner layers (maximum 3mm).

PROPERTIES

SPECIAL PROPERTIES

Easy to apply

PHYSICAL PROPERTIES	DATA
Volume Solids (%)	63 - 65
Drying time (hours)	24
Weight solids (%)	79 - 81
Weight per gallon (kg/gal)	6.12 - 6.42

CONTAINERS and COLORS

AVAILABLE CONTAINERS

¼ gallon plastic can (0.946 Lt.)

1 gallon plastic can (3.785 Lt.)

- Or By Special Order

SURFACE PREPARATION

CONDITION	INSTRUCTION
New Surface	<p>Before applying, remove any dirt, such as dust, grease, or other contaminants, using power tools, sandblasting or scarification to leave an appropriate anchoring profile.</p> <p>Remove loose or peeling old paint film with the appropriate tools. After that, wash and scrub with brush or brooms, do not use detergents.</p>

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

PEGA ALL

505-00230-000

Application Instructions

Start by softly mixing this product. Apply with a 3mm toothed trowel or spatula, leaving an even layer on the surface.

To join ceramic or porcelain tiles, tap them gently with a rubber mallet and hold the piece temporarily while the adhesive dries. To install tiling on vertical surface use wooden or similar supports until the correct adhesion develops.

Heavier decorative pieces should be propped up while the material reaches its maximum resistance (48 hours), as well as give a curing time prior to placement.

To apply on wood, it is advisable to scratch the surface with a nail or other sharp tool to obtain optimal results. To join metals together, sheets should be screwed or riveted together as a reinforcement.

This product is not sandable and should not be diluted or mixed with any other component.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Do not use this product in high temperature environments, in constant immersion or freezing conditions.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.