

TECHNICAL INFORMATION

PEGA FAST

Montage PU Glue

505-00237-002



DESCRIPTION

PEGA FAST is a polyurethane adhesive specially designed for the gluing of decorative Styrofoam moldings to other materials such as concrete, wood and metal. It can be used as a sealant for joints where a rigid sealing is required.

USE

This adhesive can glue many different materials, although its main use is to manufacture expanded polystyrene panels (EPS), joining MDF panels with polystyrene to form sandwich panels, and to glue polystyrene panels together. This adhesive can also be used to install small sizing decorative moldings (including those anchored temporarily) on concrete, Gypsum, fiber cement and wood. It's usually applied with a caulking gun, laying waving lines across the area to be glued.

Line Industrial/Professional line

PROPERTIES

SPECIAL PROPERTIES

Appearance Beige

PHYSICAL PROPERTIES

DATA

Maximum open time	30 min
Total curing time (hours)	3 - 4
Weight solids (%)	90-100
Density (kg/l)	1.37 - 1.40

CONTAINERS and COLORS

AVAILABLE CONTAINERS

9.6Fl.Oz. (283cc.) caulking gun cartridge

SURFACE PREPARATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGA FAST

Montage PU Glue

505-00237-002



CONDITION	INSTRUCTION
Surface preparation	Before applying this adhesive, remove any dirt, such as dust, grease, or other contaminant.

PRODUCT APPLICATION

Application Instructions

Cut the nozzle to make a spout of the required diameter of the adhesive strip according to the area to glue.

Try to apply the adhesive in waving lines along the surface.

Parts to be joined should be pressed in place for some 2 minutes.

In large or heavy molding or parts, use temporary anchors to keep them in place, while the adhesive develops its full strength.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all its warranties are void.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.