

TECHNICAL INFORMATION

PEGA MAX

505-00238-000



DESCRIPTION

PEGA MAX is a water-based, acrylic adhesive for bonding interior and exterior moldings, trims, baseboards, and all types of decorative panels.

USE

PEGA MAX is used to bond building elements such as trim and baseboards.

Line Industrial/Professional Line

PROPERTIES

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	57 - 60 %
Weight Solids (%)	71 - 74 %
Drying time (h)	7 Hours
Weight per gallon (kg/gal)	5.50 - 5.60 kg/gal
Touch-Dry	30 - 45 minutes

CONTAINERS

AVAILABLE CONTAINERS

Caulking gun cartridge: 300 ml.

AVAILABLE COLOR

White

SURFACE PREPARATION

CONDITION

INSTRUCTION

SURFACE PREPARATION: Before applying this adhesive, surfaces must be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT APPLICATION

Application instructions

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGA MAX

505-00238-000



Cut the nozzle at a diameter according to the size of the application required, considering the area to be glued. Adhesive should not be applied to the entire surface to be adhered, but in a wave or zig zag pattern along the surface.

A 1 - 2-minute press time of adhered parts is recommended.

On large or heavy molding trims, is advised to place temporary anchors while adhesive is fully drying. Sometimes, these anchors should be permanent.

NOTICE:

- ✓ If you need other information, visit our website at <https://www.gruposur.com/asistencia/>
- ✓ Should be used by the expiration date indicated on the package label.
- ✓ After that date, there is no guarantee that this product will maintain its adhesion properties.

HEALTH

- ✓ If you need to dispose of empty packages of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protective Equipment, as described in the respective Safety Data Sheet (MSDS), available on our website <https://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.