

TECHNICAL INFORMATION

PEGASIL

505-00239-900



DESCRIPTION

PEGASIL is a clear silicone, which serves as a surface sealant and adhesive. It is a single part product, with waterproofing and flexibility properties.

USE

Used on substrates such as glass, aluminum, marble, ceramics, and wood. Due to its thixotropy it is ideal for vertical applications as it does not run down or sag. It has excellent UV resistance, allowing it to be applied indoors and outdoors.

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance: Clear

PHYSICAL PROPERTIES

DATA

Weight Solids (%)	65 - 70
Weight per gallon (kg/gal)	3.6 - 3.7
Touch-Dry	60 min

CONTAINERS

AVAILABLE CONTAINERS

Caulking gun cartridge: 300 ml.

SURFACE PREPARATION

CONDITION

INSTRUCTION

SURFACE PREPARATION: Before applying adhesive, surfaces must be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT

MIXING RATIOS

MIXING INSTRUCTIONS

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGASIL

505-00239-900



Product: 505-00239-900, PEGASIL

Ready-to-use
product. No dilution
required

PRODUCT APPLICATION

APPLICATION TOOLS

Caulking Gun

Application instructions

Cut the nozzle at a diameter according to the size of the application required.

Be sure to tightly close the caulking cartridge at the end of application.

It is recommended to leave a small amount of product out of the nozzle so that when dried it will serve as a plug (self-sealing).

NOTICE:

- ✓ Must be used by the expiration date indicated on the package label.
- ✓ After that date, there is no guarantee that this product will maintain its adhesion properties.
- ✓ If you need other information, visit our website at <https://www.gruposur.com/asistencia/>

HEALTH

- ✓ If you need to dispose of empty packages of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protective Equipment, as described in the respective Safety Data Sheet (MSDS), available on our website <https://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.