

PLASTERFAST CONCENTRADO

Mortar Bonding Agent

505-00751-506

DESCRIPTION

PLASTERFAST CONCENTRADO is a specialized adhesive designed to promote the adhesion of plaster mortars to smooth surfaces, with a long curing time, without the need to generate an anchor profile.

USE

PLASTERFAST CONCENTRADO is used to bond mortars up to 15 mm thick to columns, walls and beams of masonry, concrete, prefabricated and other similar surfaces, in indoors or roofed outdoors areas.

Structure	Walls, fascia boards
Interior/Exterior	Indoor
Surface	Concrete
Line	Domestic, Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Translucent blue
------------	------------------

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	27 – 29
Weight Solids (%)	17 – 19
Weight per gallon (kg/gal)	3.8 – 4.0

CONTAINERS and COLORS

AVAILABLE CONTAINERS

¼ gallon can (0.946 Lt.)
4 liter can (1.06 gallon)
5 gallon can (18.925 Lt.)
55-gallon drum (208 Lt.)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



SURFACE PREPARATION

CONDITION	INSTRUCTION
Surface preparation	The surface must be clean, free of dust, grease, oil or release agent stains or any other type of contaminant.
Surface preparation	To clean release agent residue or other contaminants, the surface should be washed with soap and water and allowed to dry for 24 hours.

PRODUCT APPLICATION

Yield

:	50 – 60 m ² /gallon
---	--------------------------------

Application conditions

It should not be applied on surfaces where, due to water leaks, it flows freely, nor on concrete previously treated with another waterproofing or paint.

Not recommended for vertical veneers over lightweight drywall panels (Durock®, DensGlass®, Fiberock®) or similar.

Do not allow more than 10 days before applying mortar over this product.

Mortars applied over PLASTERFAST must not exceed 15mm thick.

Application Instructions

Hmogenize thoroughly this product.

Dilute with an equal amount of clean water (one liter of Plasterfast Concentrate for every liter of clean water).

Use brush or roller to apply evenly over surface, leaving a generous coat.

Allow to dry completely (30 to 45 minutes) before applying plaster.

Plaster should be placed the same day Plasterfast Concentrate is applied. Otherwise, Plasterfast must be protected from direct rain or possible contamination.

Do not apply over frozen, pulverized, unstable or unsound surfaces.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Plaster should be placed the same day Plasterfast Concentrate is applied. Otherwise, Plasterfast

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



must be protected from direct rain or possible contamination.

- ✓ Do not use on walls below water level or in permanent immersion, as it is re-emulsifiable.
- ✓ If the surface becomes wet prior to plastering, Plasterfast Concentrate should be reapplied.
- ✓ Do not apply on plaster whose thickness exceeds 15 mm.

HEALTH

- ✓ This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.