

TECHNICAL INFORMATION

PLASTERFAST BONDING AGENT

505-00752-506



DESCRIPTION

PLASTERFAST BONDING AGENT is a specialized ready-to-use adhesive designed to promote the adhesion of plaster mortars over smooth surfaces without the need to create an anchor pattern.

USE

Used to bond mortars up to 15mm. thick over columns, walls and beams of masonry, concrete, precast and similar surfaces, located indoors or in roofed outdoor areas. It should not be applied over walls subject to constant humidity.

Structure	Walls
Exterior/Interior	Indoor
Surface	Concrete
Product line	Domestic, Professional/industrial Line

CHARACTERISTICS

SPECIAL PROPERTIES

Easy to apply

PHYSICAL PROPERTY	DATA
Volume Solids (%)	15 - 17
Stormer Krebs Viscosity (Ku)	90 - 100
Weight solids (%)	23 - 25
Weight per Gallon (kg/gal)	3.85 - 4.05

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 2.0 of: Feb 2/24/2021
24 2021 9:36AM



TECHNICAL INFORMATION

PLASTERFAST BONDING AGENT

505-00752-506



PRESENTATION

AVAILABLE PRESENTATIONS

¼ gallon metal can (0.946 Lt.)

4 Liter

5 gallon bucket (18.925 Lt.)

55 gallon drum (208 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

New surface

Remove any residue of grease, paints or other contaminants with sandpaper, spatula, steel brush, grinding, polishing, sandblasting, high pressure washer or scarifying to obtain a suitable anchor pattern. Wash the surface with domestic tools, as brush or brooms. Do not use detergents.

PRODUCT APPLICATION

Application conditions

To apply this product, the substrate must be between 5 and 30°C.

It should not be applied on surfaces where, due to water seepage, it flows freely, nor on concrete previously treated with another type of waterproofing or paint.

Not recommended for vertical veneers over lightweight drywall panels (Durock®, DensGlass®, Fiberock®) or similar.

Do not allow more than 10 days to apply the mortar on the product.

Mortar applied on PLASTERFAST must not exceed 15 mm. thickness.

Application Instructions

Do not apply over frozen, sprayed, unstable or inconsistent surfaces.

Thoroughly blend this product.

Use a brush or roller to apply a generous, even coat.

Allow it to dry completely (30 to 45 minutes) before applying the plaster.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 2.0 of: Feb 2/24/2021
24 2021 9:36AM



TECHNICAL INFORMATION

PLASTERFAST BONDING AGENT

505-00752-506



Place the plaster in the same day that this product was applied. Otherwise, it must be protected from direct rain or possible contamination.

OBSERVATIONS

- ✓ If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com
- ✓ Do not use on plaster under constant immersion (swimming pools, tanks, retaining walls, etc.).

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR paint store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 2.0 of: Feb 2/24/2021
24 2021 9:36AM

