

TECHNICAL INFORMATION

KLASS TOP CLEANER

509-00330-900



DESCRIPTION



Solvent-based degreaser for metal, plastic and painted surfaces before painting them. It has high power to remove contaminants such as grease, oil, wax, silicone, asphalt particles, etc. The correct use of this product reduces "fisheye" and loss of adherence due to contaminants.



Containers

16 Fl. Oz., ¼ Gallon, 1 gallon

Available Colors

Transparent

SURFACE PREPARATION



Before application, surface must be free of dust, grease, oil, waxes, or any other contaminants that can affect product adherence



SUBSTRATE

FIRST CLEANING

SANDING

AFTER CLEANING

ADHERENCE ENHANCER

Iron

330 – 900

180-220/P180-
P220N/A

330 - 900

Klass Etching Primer



Aluminum

330 – 900

180-220/P180-
P220N/A

330 - 900

Klass Etching Primer

Galvanized Steel

330 – 900

Gray Fiber

330 - 900

Klass Etching Primer

OEM Finish

330 – 900

220/P220

330 - 900

Klass Primer Filler 3+1

Replacement Part

330 – 900

Gray Sponge

330 - 900

Klass Primer Filler 3+1

Paintable Plastic

330 - 900

Red Fiber

330 - 900

Klass Plastic Primer

COMPONENTS AND MIXING RATIOS



Ready to use.
Do not require any mixing



MIXING RATIO

HARDENER

DILUENT

Do not mix

N/A



Application Viscosity

N/A

Pot Life

N/A

APPLICATION EQUIPMENT



Air Spray

Nozzle

Pressure (PSI)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLASS TOP CLEANER

509-00330-900



Conventional Suction Feed

N/A

N/A

Standard Gravity Feed

N/A

N/A

Gravity Feed HVLP

N/A

N/A

PRODUCT APPLICATION



Number of coats

Time Between Coats

Dry Film Thickness

N/A

N/A

N/A



Drying Times



Data measured at 20°C (68°F). In case of contamination, lightly sand two-layer with #600 grit wet and reapply.



Drying

TIME

Forced drying

TIME

Dust dry

N/A

Oven @ 60°C:

N/A

Touch Dry

N/A

Medium wave infrared

N/A

Dry-to-sand

N/A

Short wave infrared

N/A

Before the next product

N/A

Dry to retouch

N/A

SANDING



SANDING METHOD

GRIT

FEPA GRIT

Wet sand by hand

N/A

N/A



Dry sand by hand

N/A

N/A

Power sanding, dry

N/A

N/A

OBSERVATIONS

Use this product with paper towels, chemically clean and leaving no residues, such as lint or fibers. Do not use wipes or fabric to clean, as these can be contaminated, and they also leave lint. Do not clean an area larger than one square meter at a time. Avoid cleaning the substrate in a circular shape, as this spreads contamination back and forth.

STORAGE, HEALTH AND SAFETY

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLASS TOP CLEANER

509-00330-900



Keep this product stored for a short period, in dry environment, between 50°F and 95°F.
Read and understand all safety instructions on label.



Do not use this product near sources of ignition, such as sparks or equipment with high temperatures.
Do not smoke during use. Use in a well aired area.



Never add other components than those indicated on this sheet. Doing so may affect its performance and voids all warranties.

If you need more information, check our website <https://www.gruposur.com/asistencia/>

This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

- Dispose of waste in accordance with local laws and regulations.

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.