

DESCRIPTION



Ultra Soft 17530 is a high-quality polyester resin putty designed to fill dents on automotive bodies. This product's content per container complies with American standard format. It is a fast drying, good adhesion, easy to sand and good filling product.



Available Color

White

Available containers

3.0 lt. (0.8 gallon)

0.750 lt. (0.2 gallon)

Kit (ask our representative)

SURFACE PREPARATION



Before application ensure substrate is completely free of dust, grease, wax, or other substance that may affect adhesion.



SUBSTRATE	INITIAL CLEANING	SANDING	POST CLEANING	ADHERENCE PROMOTER
Iron:	330-900	180-220/P180-P220	00330-900	N/A
Aluminum:	N/A	N/A	N/A	N/A
Galvanized:	N/A	N/A	N/A	N/A
Original Finish:	N/A	N/A	N/A	N/A
Replacement part:	N/A	N/A	N/A	N/A
Paintable Plastic:	N/A	N/A	N/A	N/A

BLENDS AND COMPONENTS



MIXING RATIO	CATALYST	Diluent
Product: 100 parts	00383-300	N/A
Hardener: 2 parts		
MIXING RATIO 100:2		

This product should be used by qualified personnel using special equipment. These technical data were calculated under controlled laboratory conditions based on our experience, but we assume no responsibility for the correct selection, compatibility, application, and use of application systems for our products. SUR QUÍMICA guarantees the quality of this product, the suitability of its characteristics and qualities, but is not responsible for the results obtained under conditions impossible to verify once the work has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Viscosity for application: N/A Pot life: 3 - 6 min

APPLICATION EQUIPMENT



Mix and apply this product with a plastic or metal putty knife, in good condition and clean.



SPRAY GUN TYPE	Nozzle size	PRESSURE (PSI)
Conventional suction feed:	N/A	N/A
Non-HVLP, gravity feed:	N/A	N/A
HVLP, gravity feed:	N/A	N/A

PRODUCT APPLICATION



NUMBER OF LAYERS	CURING TIME BETWEEN LAYERS	DRY FILM THICKNESS
Those needed	N/A	1/4" (6.35 mm)



Comments: Do not exceed recommended thickness.

Drying time



These data correspond to 20°C (68°F)



DRYING TYPE	TIME	FORCED DRYING	TIME
Dust-free:	N/A	Oven at 60°C:	N/A

This product should be used by qualified personnel using special equipment. These technical data were calculated under controlled laboratory conditions based on our experience, but we assume no responsibility for the correct selection, compatibility, application, and use of application systems for our products. SUR QUÍMICA guarantees the quality of this product, the suitability of its characteristics and qualities, but is not responsible for the results obtained under conditions impossible to verify once the work has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

ULTRA SOFT 17530



509-17530-000

Touch dry:	N/A	Medium wave infrared:	N/A
To sand:	20 - 30 min	Short Wave Infrared:	N/A
For the next product:	N/A		
For touch-up:	N/A		

SANDING



SANDING METHOD

GRIT

FEPA GRIT

Wet, by hand:

N/A

N/A



Dry, by hand:

80-120-180

P80-P120-P180

Dry, with sander:

80-120-180

P80-P120-P180

NOTICE:

This product should never be wet sanded, because this causes moisture residue that then causes oxidation, blistering, peeling, etc. Use only sandpaper grits #80 or higher; otherwise, streak marks can be visible in the final appearance.

HEALTH

This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

Read and understand all safety indications on the package label.

Never add another component other than the one listed on this sheet. Doing so affects this product's performance and completely voids all warranties.

STORAGE AND CARE CONDITIONS



This product must be stored for short periods of time, out of reach of children, tightly closed, in dry conditions, between 10 and 35°C to avoid loss of its properties.

If you need more information, check our website <https://www.gruposur.com/asistencia/>



Exposure unprotected can result in serious health damage.

Dispose of waste in accordance with local laws and regulations.



If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

This product should be used by qualified personnel using special equipment. These technical data were calculated under controlled laboratory conditions based on our experience, but we assume no responsibility for the correct selection, compatibility, application, and use of application systems for our products. SUR QUÍMICA guarantees the quality of this product, the suitability of its characteristics and qualities, but is not responsible for the results obtained under conditions impossible to verify once the work has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

This product should be used by qualified personnel using special equipment. These technical data were calculated under controlled laboratory conditions based on our experience, but we assume no responsibility for the correct selection, compatibility, application, and use of application systems for our products. SUR QUÍMICA guarantees the quality of this product, the suitability of its characteristics and qualities, but is not responsible for the results obtained under conditions impossible to verify once the work has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions, or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.