

TECHNICAL INFORMATION

KIT ACRÍLICO

Artistic Paint Kit

522-00126-000



DESCRIPTION

Kit of 12 colors of water-based acrylic paints for artistic use, made with pigments of excellent quality and resistance. Its thick consistency prevents spills if the container is overturned.

USE

Ideal to perform various artistic techniques on paper, canvas, cardboard, fabric and wood. They have excellent elasticity, a very important concern for handling, transporting or storing the canvases.

Use it on fabric, canvas, etc.

Surface Aluminum, Concrete, Wood, Bond Paper, Art Paper, Metal, Leather, Plastic

Line Artistic Line

PROPERTIES

SPECIAL PROPERTIES

Appearance

Good color intensity

Fast drying

Easy to apply

Excellent quality

Ready to use

Weather Resistance



PHYSICAL PROPERTIES

DATA

Drying Time 10 minutes (depending on film thickness)

CONTAINERS

AVAILABLE CONTAINERS

Kit of 12 metallic tubes with 12 ml. each

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KIT ACRÍLICO

Artistic Paint Kit

522-00126-000



PRODUCT PREPARATION

| COMPONENT | MIXING RATIO | MIXING INSTRUCTIONS |
|--------------------------------------|--------------------|---------------------|
| Product: 522-00126-000, KIT ACRÍLICO | 100 parts | |
| Diluent: Tap Water | 0 – 5 parts | |

For better results, use distilled water to dilute and mix.

PRODUCT APPLICATION

APPLICATION TOOL

Brush

Sponge

Paint brush

Roller or Putty knife

Drying Times

Open time or touch-dry is from 5 to 7 minutes.

Full drying time is from 15 to 20 minutes.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ Do not apply under direct sunlight, to avoid a faster drying.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.