

TECHNICAL INFORMATION

KIT DE ÓLEO ARTISUR

Oil Paint Kit

522-00151-000



DESCRIPTION

Kit de Óleo Arti Sur contains 6 colors made with pigments of excellent quality and intense colors agglutinated with natural drying linseed oil with high UV resistance. White paint was made with non-yellowing oils.

USE

Ideal for applying on canvas, wood, heavy-weight papers and cardboard. Long-lasting, designed especially for artistic use.

Surface Canvas

Line Artistic Line, Domestic Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Satin				
Long-lasting					
Excellent quality					
Good color intensity					
Easy to apply					
Hiding Power	●	●	●	●	●
Weather Resistance	●	●	●	○	○

PHYSICAL PROPERTIES

DATA

Weight solids (%)	98 - 100
Brookfield Viscosity (cPs)	100.000 - 200.000
Volume Solids (%)	98 - 100

CONTAINERS

AVAILABLE CONTAINERS

Kit with 6 tubes, 40 ml. (1.4 fl. oz.) each.

AVAILABLE COLORS

White 000

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Dec 12/18/2020
18 2020 8:42AM



TECHNICAL INFORMATION

KIT DE ÓLEO ARTISUR

Oil Paint Kit

522-00151-000



Light cadmium yellow 100

Cadmium red 300

Blue Phtalo 524

Permanent light green 605

Black 700

SURFACE PREPARATION

CONDITION	INSTRUCTION
Surface preparation:	Surface should be dry and free of grease, oil, dust, or any other contaminants.
Surface preparation:	Surface should free of contaminants and prepared with GESSO ARTISUR.

PRODUCT PREPARATION

COMPONENTE	MIXING RATIO	MIXING INSTRUCTIONS
Product: 522-00151-000 Kit Óleo ArtiSur	100%	
Diluent: 522-00362-900, ACEITE LINAZA	5% + 5%	Dilute with 5% of Aceite Linaza (522-00362-900) and another 5% of Diluyente Orgánico 52200458-900 for an easier application.
Diluent: 522-00458-900 DILUYENTE ORGÁNICO ARTISUR	10%	Use 10% for a better transparency and a faster drying.

Use the same diluent for brushes and equipment washing.

PRODUCT APPLICATION

APPLICATION TOOL

Brush Putty Knife Paintbrush

Tools

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Dec 12/18/2020
18 2020 8:42AM



TECHNICAL INFORMATION

KIT DE ÓLEO ARTISUR

Oil Paint Kit

522-00151-000



The product can be applied with brush, paintbrush or putty knife.

Application Conditions

This product should not be applied directly exposed to sunrays, rain, fog or strong winds.

Drying times

Touch-Dry time	24 - 72 hours (depending on film thickness)
----------------	---

Application Instructions

Arrange the canvas on a wooden board or canvas frame where it can be fixed and stretched at the artist's convenience.

Before applying, prime the surface using the NEUTRAL GESSO ARTI SUR 522-01262-900 or GESSO ARTI SUR BLANCO 522-01262-000 to leave a very fine background, to avoid cracking.

Proceed with oil paint application, either using the "*alla prima*" technique (wet-on-wet) or by layers (at least one below and one on top of that).

To dilute this paint, use DILUYENTE ORGÁNICO ARTI SUR 522 00458 900.

If you need an increased gloss and an easier application, use ACEITE DE LINAZA ARTI SUR 522-00362-900. arti sur flaxseed oil 522-00362-900.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Dec 12/18/2020
18 2020 8:42AM

