

TECHNICAL INFORMATION

GESSO NEUTRO ARTISUR

Neutral Gesso

522-01262-900



DESCRIPCIÓN

GESSO NEUTRO ARTI SUR is a clear acrylic priming coat for artistic purposes; it's flexible, durable and fast drying.

USE

GESSO NEUTRO ARTI SUR is used for preparation or priming different substrates, as canvas, wood, cardboard, or MDF. Being a clear background, it can be mixed with acrylic paints to get colored priming of high intensity and great adherence.

Surface Canvas, Wood, Cardboard, MDF

Line Artistic Line, Domestic Line

PROPERTIES

SPECIAL PROPERTIES

Long-lasting

Excellent quality

Easy to apply

Ready to use

Fast drying

Outdoor Resistance



PHYSICAL PROPERTIES

DATA

Weight per gallon (kg/gal)	4.20 – 4.40
Viscosity (cPs)	20000 – 25000
Weight solids (%)	55 – 57
Volume Solids (%)	45 – 47
pH	7 – 9

CONTAINERS

AVAILABLE CONTAINERS

250 ml. (8.5 Fl. Oz.)

AVAILABLE COLORS

Colorless

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:56AM



TECHNICAL INFORMATION

GESSO NEUTRO ARTISUR

Neutral Gesso

522-01262-900



1 liter (1.06 qt.)

SURFACE PREPARATION

CONDITION	INSTRUCTION
Surface preparation	Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 522-01262-900, GESSO NEUTRO ARTISUR	100%	Stir well before use
Diluent: Tap Water	10% - 15%	

PRODUCT APPLICATION

APPLICATION TOOL

Brush Paintbrush Roller

Application Conditions

This product should not be applied directly exposed to sunrays, rain, fog, or strong winds.

Number of coats and thickness

Coats	Apply 1 to 3 coats
-------	--------------------

DRYING TIMES

Touch-Dry (@ 6 mils)	Canvas or Cardboard: 7 - 10 minutes MDF: 20 - 25 minutes
Full drying time (@ 6 mils)	Canvas or Cardboard: 10 - 15 minutes MDF: 25 - 35 minutes

Application instructions

Apply the product on the surface to be prepared, using brush, paintbrush or roller, changing direction

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:56AM



TECHNICAL INFORMATION

GESO NEUTRO ARTISUR

Neutral Gesso

522-01262-900



of application between each layer.

Equipment cleaning

Wash tools used with tap water.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:56AM

