

TECHNICAL INFORMATION

GESSO BLANCO ARTISUR

White Gesso

522-01262-000



DESCRIPTION

GESSO BLANCO ARTI SUR is a white acrylic priming coat for artistic purposes; it's flexible, durable and fast drying, and enhances the intensity of colors applied over it.

USE

GESSO BLANCO ARTI SUR is used for preparation or priming different substrates, as canvas, wood, cardboard, or MDF, generating better adhesion between paint and surface, enhancing color intensity, and providing protection and durability to the artwork.

Surface	Canvas, Wood, Cardboard, MDF
---------	------------------------------

Line	Artistic Line, Domestic Line
------	------------------------------

PROPERTIES

SPECIAL PROPERTIES

Long-lasting

Excellent quality

Easy to apply

Ready to use

Fast drying

Outdoor Resistance



PHYSICAL PROPERTIES

DATA

Weight per gallon (kg/gal)	4.9 – 5.1
Weight solids (%)	60 – 62
Viscosity (cPs)	45.000 – 50.000
Volume Solids (%)	47 – 49
pH	7 – 9

CONTAINERS

AVAILABLE CONTAINERS

250 ml. (8.5 Fl. Oz.)

AVAILABLE COLORS

White

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:50AM



TECHNICAL INFORMATION

GESSO BLANCO ARTISUR

White Gesso

522-01262-000



1 liter (1.06 qt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface preparation

Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT

MIXING RATIO

MIXING INSTRUCTIONS

Producto: 522-01262-000, GESSO BLANCO 100%
ARTISUR

Stir well before use

Diluent: Tap Water

10% - 15%

PRODUCT APPLICATION

APPLICATION TOOL

Brush

Paintbrush

Roller

Application Conditions

This product should not be applied directly exposed to sunrays, rain, fog, or strong winds.

Number of coats and thickness

Coats

Apply 1 to 3 coats

DRYING TIMES

Touch-Dry (@ 6 mils)

Canvas or Cardboard: 7 - 10 minutes

MDF: 20 - 25 minutes

Full drying time (@ 6 mils)

Canvas or Cardboard: 10 - 15 minutes

MDF: 25 - 35 minutes

Application instructions

Apply the product on the surface to be prepared, using brush, paintbrush or roller, changing direction of application between each layer.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:50AM



TECHNICAL INFORMATION

GESSO BLANCO ARTISUR

White Gesso

522-01262-000



NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 2.0 del: Feb 2/19/2021
19 2021 8:50AM

