

TECHNICAL INFORMATION

PINTURA ARTESANAL

Handicraft Paint



522-22020-000

DESCRIPTION

Pintura Artesanal 522-22020-000 is a water-based acrylic handicraft paint, easy-to-apply, made with excellent quality pigments.

USE

Specially designed for artistic use, handicraft and artisans. It can be applied on canvas, cardboard, paper, glass, MDF, wood or raw ceramic.

Exterior/Interior Surface	Canvas, Wood, MDF
Line	Artistic Line, Domestic Line

CHARACTERISTICS

SPECIAL PROPERTIES

Finish	Matte
Long Lasting	
Excellent Quality	
Fast Drying	
Easy to Apply	
High Intensity colors	
Ready to Use	
Hiding Power	3 / 5
Weather Resistance	3 / 5

PHYSICAL PROPERTY

DATA

Weight solids (%)	54 - 56
Weight per Gallon (kg/gal)	4.9 - 5.1
Volume Solids (%)	38 - 40
pH	7 - 9
Shelf Life	3 years
Stormer Krebs Viscosity (Ku)	110 - 120

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 7.0 de
apr 27 2021



TECHNICAL INFORMATION

PINTURA ARTESANAL

Handicraft Paint



522-22020-000

PRESENTATION

AVAILABLE PRESENTATIONS

120 mL. Plastic container

1Lt. Plastic container

AVAILABLE COLORS

Available in chart colors

PRODUCT PREPARATION

COMPONENT

MIXING RATIO

MIXING INSTRUCTIONS

Product: 522-22020-000, PINTURA
ARTESANAL

100%

Stir well before use.

It can be diluted with up to 10% of tap water, for an easier application.

PRODUCT APPLICATION

IT CAN BE APPLIED WITH

Paintbrush



Brush



Roller

Brushing

This product can be applied with roller, brush or paintbrush

Application conditions

Avoid that the product in its application stage is exposed directly to the sun, rain, mist or strong winds.

To achieve a better finish, the surface should be prepared with GESSO ARTI SUR (522-01262-000 / 900).

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 7.0 de
apr 27 2021



TECHNICAL INFORMATION

PINTURA ARTESANAL

Handicraft Paint



522-22020-000

Drying times

Dry-to-Touch Time	5 - 7 minutes (@ 3 mils)
Complete drying time	15 - 20 minutes (@ 3 mils)

Drying times listed are under ideal conditions (Between 22–28°C temperature and 50 – 80% relative humidity). These times are dependent on temperature, moisture, film thickness and dilution.

OBSERVATIONS

Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
If you need more information, check our website <https://www.gruposur.com/asistencia/>

HEALTH

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

User of this product may need to wear the appropriate Personal Protective Equipment, as described in its Safety Data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 7.0 de
apr 27 2021

