

# TECHNICAL INFORMATION

## PEGAFORTE ADHESIVO INDUSTRIAL 140

525-23140-000



### DESCRIPTION

PEGAFORTE ADHESIVO INDUSTRIAL 140 is a high solid, fast drying, excellent adhesion industrial EVA (Ethyl-vinyl acetate) adhesive. Specially formulated to bond different types of printing papers, coated or uncoated.

### USE

Adhesive developed for the assembly of folding boxes, using disc application, where the papers eventually have a protective coating and fast drying is required to allow high production speeds.

Line Industrial/Professional Line

### PROPERTIES

#### SPECIAL PROPERTIES

**Appearance:** Milky liquid.

#### PHYSICAL PROPERTIES

#### DATA

Weight Solids (%)	55 - 57
Brookfield Viscosity (cPs)	3000 - 3,600
pH	5 - 6

### CONTAINERS

#### AVAILABLE CONTAINERS

5-gallon bucket (18.925 Lt.)  
55-gallon plastic drum (220 kg)  
1000-liter tote tank

### SURFACE PREPARATION

#### CONDITION

#### INSTRUCTION

**SURFACE PREPARATION:** Before applying adhesive, surfaces must be dry and free of grease, oil, dust, or any other contaminants.

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## PEGAFORTE ADHESIVO INDUSTRIAL 140

525-23140-000

**Pegaforte**  
Adhesivos

---

### PRODUCT APPLICATION

#### Application conditions

Injection.

Application via disks, both bottom and overhead disks

---

#### NOTICE:

- ✓ To maintain its good performance, this product must be stored in a ventilated, cool, indoor area in its original, tightly closed container.
- ✓ Must be used by the expiration date indicated on the package label.
- ✓ After that date, there is no guarantee that this product will maintain its adhesion properties.
- ✓ A change in environmental conditions can significantly affect its open time and drying characteristics.
- ✓ If the adhesive remains at rest for a long time, it is recommended that it be shaken prior to use.
- ✓ If you need other information for safe handling of this product, you can visit our website <https://www.gruposur.com/asistencia/>

#### HEALTH

- ✓ The user of this product may need the appropriate Personal Protective Equipment, as described in the respective Safety Data Sheet (MSDS), available on our website <https://www.gruposur.com>
- ✓ If you need to dispose of empty packages of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose.

---

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.