

TECHNICAL INFORMATION

PEGAFORTE INDUSTRIAL ADHESIVE 151

525-23151-000



DESCRIPTION

Pegaforte Industrial Adhesive 151 was specially developed to laminate decorative paper over cardboard. It has an optimal viscosity to be used in automatic machines, where the adhesive is applied by rollers. It has excellent adhesion on paper, as well as fast drying.

USE

Specially designed for the automated book binding industry.

Product line Professional/industrial Line

CHARACTERISTICS

PHYSICAL PROPERTY	DATA
Weight solids (%)	42 - 45
Weight per Gallon (kg/gal)	3.95 - 4.20
Brookfield Viscosity RFV (cPs)	2800 - 3500 @ 25°C
Zahn Cup Viscosity @ 4 s	100 - 200 @ 25°C
pH	3 - 5

PRESENTATION

AVAILABLE PRESENTATIONS

55 gallon (208.175 liter) plastic drum

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 525-23151-000, PEGAFORTE INDUSTRIAL ADHESIVE 151	100%	Ready to use. Do not dilute.

PRODUCT APPLICATION

IT CAN BE APPLIED WITH

Brush

Roller



Spatula or Throwel

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE INDUSTRIAL ADHESIVE 151

525-23151-000



Tools

It can be applied by brush, spatula, roller, trowel or automated machine.

OBSERVATIONS

- ✓ If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com
- ✓ Store the product in its closed, sealed original container between 20°C and 30°C in a dry and ventilated place, far from sunlight, out of the reach of children.
- ✓ Changes in environmental conditions can significantly affect open time and drying characteristics.
- ✓ Manage your inventory, use first those containers with earlier expiration date, as indicated by its label. After expiration date, there is no guarantee that the product will retain its properties.
- ✓ If adhesive remains static for a long time, stir it before use.

HEALTH

- ✓ Not to be sold to minors, inhalation may cause harmful health effects, and cause dependence habit.
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.