

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 162

525-23162-000



DESCRIPTION

Pegaforte Adhesivo Industrial 162 meets the requirements of machine or manual labeling processes, using overlapping paper labels, commonly used in the food industry packaging and others. It generates an adequate initial paper to paper adhesion, which allows both ends to stay together, allowing their manipulation in a short time.

USE

Industrial Paper on Paper Adhesive is especially recommended for high-speed labeling automatic machines, on drop injection application with pressurized type systems. Before using it in any particular process, its suitability should be checked beforehand.

Line Industrial/Professional

CARACTERÍSTICAS PROPERTIES

SPECIAL PROPERTIES

Appearance	Milky liquid
-------------------	--------------

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	35 - 38
Weight solids (%)	38 - 41
Brookfield Viscosity (cPs)	25 000 - 29 000
Density (kg/l)	1.06 - 1.11
pH	3.0 - 5.0

CONTAINERS

AVAILABLE CONTAINERS

5-gallon plastic bucket (18.925 Lt.)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 162

525-23162-000



SURFACE PREPARATION

CONDITION

INSTRUCTION

SURFACE PREPARATION

Before applying the adhesive, surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PREPARACIÓN DEL PRODUCTO

COMPONENT

MIXTURE RATIO

MIXING INSTRUCTIONS

Product: 525-23162-000
ADHESIVO INDUSTRIAL 162

PEGAFORTE 100%

Ready to use, do not dilute.
Stir well before use.

PRODUCT APPLICATION

APPLICATION TOOLS

Brush Injection equipment Roller

TOOLS

Roller, Brush or injection systems, using the appropriate nozzles.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed, indoors, away from sunlight, in a fresh, ventilated place, to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. All guarantees are void after that date.
- ✓ Stir well before using, specially, if it has been a stored for a long time
- ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.

HEALTH

- ✓ This a professional/industrial product and it should be applied by properly trained personnel,

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 162

525-23162-000



wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.