

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 164

Printing Adhesive

525-23164-000



DESCRIPTION

El Pegaforte Adhesivo Industrial 164 is special for gluing printing papers. It has an ideal viscosity for application by discs in an automatic machine, or in hand application, with excellent adhesion and fast drying.

Due to its composition, it has excellent flexibility and elongation, as well as a good adhesion on surfaces waterproofed with some aqueous varnish.

USE

Use it in manual application or in an automatic machine. It has good performance when applied by discs, both lower or aerial, without suffering from runoffs or spills.

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Milky liquid
-------------------	--------------

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	37 - 39
Weight solids (%)	40 - 43
Brookfield Viscosity (cPs)	3700 - 4100
Density (kg/l)	1.02 - 1.10
pH	3 - 6

CONTAINERS

AVAILABLE CONTAINERS

5-gallon bucket (18.925 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 164

Printing Adhesive

525-23164-000



Surface preparation Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 525-23164-000, PEGAFORTE ADHESIVO INDUSTRIAL 164		Ready to use, do not dilute

Stir well before use

PRODUCT APPLICATION

APPLICATION TOOL

Brush Automated machinery Roller

Application Conditions

It can be applied by discs, both aerial or inferiors.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all its warranties are void.
- ✓ If this adhesive has been at rest for a long time, it should be stirred before use.
- ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose
 - ✓ This is a professional/industrial product and it should be applied by properly trained personnel,
-

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 164

Printing Adhesive

525-23164-000



wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.