



DESCRIPTION

Pegamento Pisos Vinílicos 525-23185-100 is a vinyl floor glue developed for manual application, where wide ranges of open times are needed, which allows its application in large areas, to then place the vinyl material.

USE

An adhesive for gluing vinyl floors on concrete and other surfaces. It can be used to glue different vinyl materials, such as tiles, rigid, flexible strands or rolled ones, on large areas where, in first place, adhesive is to be applied and, just then, the vinyl material will be placed and finally position the material. The application should be done with a toothed trowel (Teeth: 1/32 H x 1/16 W and spaced 5/64 apart)

Once the adhesive has been applied over the entire area to be covered, it should be left long enough until the adhesive darkens and gets tacky, to cover with the vinyl material.

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Creamy yellow viscous liquid
-------------------	---------------------------------------

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	45 - 49
Weight solids (%)	45 - 51
Weight per gallon (kg/gal)	3.80 - 4.35
Brookfield Viscosity (cPs)	30000 - 55.,000
Touch-dry time (minutes)	90 - 120 minutes to get "tacky".
Density (kg/l)	1,00 - 1,15
Open Time (hours)	24 hours maximum to

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE PEGAMENTO PISOS VINÍLICOS

Vinyl Floor Adhesive

525-23185-100



place vinyl material

pH

8.7 - 9.7

CONTAINERS

AVAILABLE CONTAINERS

¼ gallon can (0.946 Lt.)

1 gallon can (3.785 Lt.)

SURFACE PREPARATION

CONDITION	INSTRUCTION
Surface preparation	Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 525-23185-100, PEGAMENTO PISOS VINILICOS	PEGAFORTE 100%	Stir well before use

PRODUCT APPLICATION

APPLICATION TOOL

Toothed trowel

Application Conditions

Surface of the concrete or substrate where the vinyl material will be placed must be very smooth, level and dry. Do not use on concrete with excessive moisture or high alkalinity. Some other concrete treatments can affect adherence.

This adhesive must be strongly stirred before use, to have a better performance.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE PEGAMENTO PISOS VINÍLICOS

Vinyl Floor Adhesive

525-23185-100



Drying time

Deje pasar 5 días después de la instalación antes de humedecer el piso.

After applying the adhesive, the time to place the vinyl material should not be more than 24 hours.

Drying time depends on environmental conditions, so temperature, drafts, ambient humidity and application film thickness have a direct effect on this adhesive open time.

Before this adhesive dries up, it can be removed with soap and water, after drying, use diluent 510-00456-900.

Wait for 5 days before moisten the floor.

Application Instructions

By its nature, this adhesive will maintain the application profile.

First, apply the adhesive with a toothed trowel (Teeth: 1/32 H x 1/16 W and spaced 5/64 apart) and let enough time to get tacky (90 - 120 min) and then place the material, applying enough pressure so the adhesive correctly moisturizes the surface of the vinyl.

Then let it cure.

NOTICE

- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all its warranties are void.
- ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.
- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ If this adhesive has been at rest for a long time, it should be stirred before use.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose
- ✓ This a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.