

TECHNICAL INFORMATION



PEGAFORTE ADHESIVO DE CASEINA

525-23195-001

DESCRIPTION

Industrial Casein Adhesive 23195-001 is water based, especially suitable to adhere paper labels on glass. It offers regulated viscosity, ideal for fast adhesion and medium-speed drying. It can be applied manually or with an automatic machine. Its wetting characteristics have been modified to improve adhesion on difficult surfaces. Manufactured under ISO 14001 environmental and ISO 9001 quality certification.

USE

Specially developed for automated labeling of glass vessels with paper labels.

Product line Professional/industrial Line

CHARACTERISTICS

ASSESSMENT

Finish Viscous liquid ,
cream yellow .

PHYSICAL PROPERTY

DATA

Weight solids (%)	36 - 43
Weight per Gallon (kg/Gl)	4,0 - 4,2
Brookfield Viscosity RFV (cPs)	24,000 - 50,000
Density (kg / l)	1,06 - 1,11
pH	7,5 - 8,8

PRESENTATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over the conditions, tools, the skills of the applicator, or over the selection, preparation or compatibility of the products used; therefore can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.

TECHNICAL INFORMATION



PEGAFORTE ADHESIVO DE CASEINA

525-23195-001

AVAILABLE PRESENTATIONS

20 kg plastic bucket (16.5 lt)

OBSERVATIONS

- If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com
- Manage your inventory, use first those containers with earlier expiration date, as indicated by its label.
- After expiration date, there is no guarantee that the product will retain its properties.
- Changes in environmental conditions can significantly affect open time and drying characteristics.
- Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- Store the product in its closed, sealed original container between 20°C and 30°C in a dry and ventilated place, far from sunlight, out of the reach of children.
- In low temperatures or high humidity environment, you can get longer drying times.
- If adhesive remains static for a long time, stir it before use.

HEALTH

- For a safe use of this product ask for its safety data sheet (MSDS).
- The applicator must use the appropriate Personal Protective Equipment, which is detailed in the MSDS of this product
- If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over the conditions, tools, the skills of the applicator, or over the selection, preparation or compatibility of the products used; therefore can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.