

# TECHNICAL INFORMATION

## GOMA BLANCA ARTISUR

White Glue

525-23340-000



### DESCRIPTION

GOMA BLANCA ARTISUR is a liquid adhesive for multiples uses, especially suitable for gluing paper, wood, or cardboard. Fast drying and excellent adhesion.

### USE

GOMA BLANCA ARTISUR is ideal for direct application on handy craft, woodcrafts or similar surfaces. An excessively thick coat or low temperatures will delay its drying time.

**Surface** Bond Paper, Wood, cardboard, MDF

**Line** Domestic Line, Artistic Line

### PROPERTIES

#### SPECIAL PROPERTIES

Ready to use

Long Lasting

Excelent Quality

Fast Drying

Easy to Apply

#### PHYSICAL PROPERTIES

#### DATA

pH	4 - 6
Weight solids (%)	41 - 43
Weight per gallon (kg/gal)	3.9 - 4.1
Brookfield Viscosity (cPs)	18000 - 22000
Volume Solids	40 - 42

### CONTAINERS

#### AVAILABLE CONTAINERS

1 liter can

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Oct 10/26/2017  
26 2017 2:19PM



# TECHNICAL INFORMATION

## GOMA BLANCA ARTISUR

White Glue

525-23340-000



### SURFACE PREPARATION

#### CONDITION

#### INSTRUCTION

Surface preparation

Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

### PRODUCT PREPARATION

#### COMPONENT

#### MIXING RATIO

#### MIXING INSTRUCTIONS

Product: 522-23340-000, GOMA BLANCA 100%  
ARTISUR

Ready to use, do not dilute

### PRODUCT APPLICATION

#### APPLICATION TOOL

Direct from the plastic Finger  
can

Spatula/Sponge

Brush

### Application conditions

Protect this product from sunrays, rain, mist or strong winds during its application.

Do not apply when relative humidity exceeds 85%, when raining or with direct rain threat for the next few hours

Surface moisture:

Wood: 16% maximum

Drying Time:

When joining wood corners, edges or sides, give a minimum allow of 2 hours setting time before handling the parts.

Total drying time:

Paper and cardboard: 15 - 20 minutes (@ 6mils film thickness)

Drying times listed are under ideal conditions (Between 22-28°C temperature and 50 - 80% ambient humidity). These times are dependent on temperature, moisture, film thickness and dilution.

### APPLICATION INSTRUCTIONS

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Oct 10/26/2017  
26 2017 2:19PM



# TECHNICAL INFORMATION

## GOMA BLANCA ARTISUR

White Glue

525-23340-000



---

This product is designed to apply with fingers, brush or sponge on paper, cardboard, wood or MDF, which are then joined in the desired position and allowed to dry.

Washable with soap and water, while wet.

If it comes in contact with fabric, it should be washed immediately before the product dries, to avoid permanent stains.

---

### NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>

### HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose

---

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Oct 10/26/2017  
26 2017 2:19PM

