

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO PARA PANELES DE

POLIESTIRENO

PEGAFORTE ADHESIVE FOR POLYSTYRENE PANELS



525-23391-000

DESCRIPTION

Adhesive for Expanded Polystyrene Panels 23391-000 is a high-solid content, water-based acrylic with evaporative drying, which has excellent adhesion to expanded styrene sheets and other surfaces. For a correct curing, one of the adhered substrates must be water absorbent.

USE

Use on expanded polystyrene panels, joining expanded polystyrene to concrete or wood. It presents a good performance in the bonding of vinyl floors to wood and concrete. Once cured it is resistant to moisture.

Product line Professional/industrial Line

CHARACTERISTICS

SPECIAL PROPERTIES

Appearance

Thixotropic
paste (High
viscosity when
the product is at
rest, but
decreases when
mixed or stirred)

PHYSICAL PROPERTY

DATA

Weight per Gallon (kg/gal)

4.20 - 4.40

Stormer Krebs Viscosity (Ku)

110 - 140

PRESENTATION

AVAILABLE PRESENTATIONS

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 1.1 of: Jun 1 6/1/2017
2017 9:33AM



TECHNICAL INFORMATION

PEGAFORTE ADHESIVO PARA PANELES DE

POLIESTIRENO

PEGAFORTE ADHESIVE FOR POLYSTYRENE PANELS



525-23391-000

¼ gallon can (0.946 Lt.) = 1 kilogram

1 gallon can (3.785 Lt.) = 4 kilograms

5 gallon bucket (18.925 Lt.) = 20 kilogramos.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product : 525-23391-000 PEGAFORTE Adhesive for Expanded Polystyrene Panels	100%	Ready to use. Do not require dilution.

Before use, mix thoroughly and then add diluent.

PRODUCT APPLICATION

IT CAN BE APPLIED WITH



Square notch trowel.

Application conditions

Once the surfaces are prepared, apply the product with a toothed trowel.

Expanded polystyrene panels: Do not use on surfaces exposed to very high temperatures or high moisture content, as this may affect penetration on the substrate and the integrity of the joint.

Application Instructions

Bond firmly glued parts in final position and let dry.

It can be applied manually.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 1.1 of: Jun 1 6/1/2017
2017 9:33AM



TECHNICAL INFORMATION

PEGAFORTE ADHESIVO PARA PANELES DE

POLIESTIRENO

PEGAFORTE ADHESIVE FOR POLYSTYRENE PANELS



525-23391-000

OBSERVATIONS

- ✓ If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com
- ✓ Store the product in its closed, sealed original container between 20°C and 30°C in a dry and ventilated place, far from sunlight, out of the reach of children.
- ✓ In low temperatures or high humidity environment, you can get longer drying times. Changes in environmental conditions can significantly affect open time and drying characteristics
- ✓ Manage your inventory, use first those containers with earlier expiration date, as indicated by its label. After expiration date, there is no guarantee that the product will retain its properties.
- ✓ If adhesive remains static for a long time, stir it before use.

HEALTH

- ✓ The user may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 1.1 of: Jun 1 6/1/2017
2017 9:33AM

