

TECHNICAL INFORMATION

POXIFORTE ADHESIVO EPÓXICO GRIS

Gray Epoxy Adhesive

525-23410-720



DESCRIPTION

POXIFORTE Gris is a two-part adhesive with excellent bonding strength, great resistance and durability, ideal for household, workshop, garage and crafts fixes and repairs. Easy to mix and use.

USE

Formulated as a multiple application adhesive. It serves to repair, fix, build and seal. Ideal for filling gaps, voids, marks or missing pieces.

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Gris
------------	------

PHYSICAL PROPERTIES

DATA

Weight solids (%)	100%
-------------------	------

CONTAINERS

AVAILABLE CONTAINERS

70ml kit containing: 35ml Component A + 35ml Component B + Palette and mixing stick.

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface preparation	Surfaces should be dry and free of grease, oil, dust, or any other contaminants.
---------------------	--

PRODUCT PREPARATION

COMPONENT

MIXING RATIO

MIXING INSTRUCTIONS

Product: 525-23410-720, Poxiforte Adhesivo 50% each component Pour equal parts of each

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Oct 10/9/2017
9 2017 2:09PM



TECHNICAL INFORMATION

POXIFORTE ADHESIVO EPÓXICO GRIS

Gray Epoxy Adhesive

525-23410-720



Epóxico Gris

(1:1)

Component in the mixing palette and stir with the kit's mixing stick to get a uniform mixture.

PRODUCT APPLICATION

APPLICATION TOOL

Manual Use

Application instructions

Mix both parts as Instructed above and apply the mixture in both parts to be glued together.

Join both parts and keep under pressure for some 10 minutes.

Let it cure for 2 hours.

Reach its maximum bonding strength in 24 hours

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight and extreme heat, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all guarantees are void.
- ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Oct 10/9/2017
9 2017 2:09PM

