

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 910

525-23755-910



DESCRIPTION

Pegaforte Adhesivo Industrial 910 is an adhesive designed for one of the steps on the industrial production of PVC ceiling sheets.

USE

This adhesive is applied on the PVC sheet to prepare it for the adherence of a decorative film of the same material, which will be applied with another adhesive. This is an industrial process done in a roller machine.

Line Industrial/Professional

CARACTERÍSTICAS PROPERTIES

SPECIAL PROPERTIES

Form	Clear liquid
------	--------------

PHYSICAL PROPERTIES

DATA

Weight per gallon (kg/gal)	3.5 - 3.7
Brookfield Viscosity (cPs)	300 - 450
Weight solids (%)	17 - 21%

CONTAINERS

AVAILABLE CONTAINERS

5-gallon plastic bucket (18.925 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface preparation: Surface should be dry and free of grease, oil, dust or any other contaminants.

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 910

525-23755-910



Application instructions

This product should be applied in a constant thickness film by an automatic roller machine. This adhesive open time should be controlled (from the moment it is applied until the decorative film is set on top of it and pressured).

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a cool, ventilated place, away from sunlight, to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose
- ✓ This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.