

TECHNICAL INFORMATION

PEGAFORTE ADHESIVO INDUSTRIAL 920

525-23755-920



DESCRIPTION

Pegaforte Adhesivo Industrial 920 is an adhesive for industrial production of PVC decorative ceiling sheets.

USE

This adhesive is used in the second step of the industrial roller machine, over the decorative PVC film, so that it sticks to the adhesive previously applied on the smooth sheet, resulting in a decorated PVC panel.

Line Industrial/Professional

PROPERTIES

SPECIAL PROPERTIES

Form	Transparent liquid
------	--------------------

PHYSICAL PROPERTIES

DATA

Weight per gallon (kg/gal)	3.5 - 3.7
Brookfield Viscosity (cPs)	100 - 300
Weight solids (%)	16 - 18%

CONTAINERS

AVAILABLE CONTAINERS

5-gallon bucket (18.925 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface preparation	Surface should be dry and free of grease, oil, dust or any other contaminants.
---------------------	--

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Application Instructions

This product should be applied in a uniform thickness by an automatic roller machine, controlling its open time, from the moment its applied to the decorative vinyl film and pressure is applied.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place away from sunlight, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label.

HEALTH

- ✓ This a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.