

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO

Contact Cement

525-23792-100



DESCRIPTION

Pegaforte Cemento de Contacto 23792-100 is a professional use glue, developed for leather and furniture industries. It has excellent adhesion, excellent leveling and moisture resistance, its viscosity has been improved to apply on porous or very absorbent surfaces.

USE

This cement can be used to glue materials such as wood, leather, carpets, formica, or foam. However, given the wide variety of materials that could be adhered, the user should do the relevant confirmatory tests.

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Viscous liquid
-------------------	----------------

PHYSICAL PROPERTIES

DATOS

Volume Solids (%)	13- 14
Specific density (g/ml)	0.83 - 0.86
Weight solids (%)	20 - 22
Brookfield Viscosity (cPs)	2.500-4.500

CONTAINERS

AVAILABLE CONTAINERS

55-gallon drum (208 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO

Contact Cement

525-23792-100



Surface preparation Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT

MIXING RATIO

MIXING INSTRUCTIONS

Product: 525-23792-100, PEGAFORTE 100 % Ready to use, do not dilute
CEMENTO DE CONTACTO

PRODUCT APPLICATION

APPLICATION TOOL

Brush

Putty knife

Application Conditions

A very humid environment could affect adhesion.

This product must be applied on both sides for a proper adherence.

Drying time

El secado abierto o al tacto es de 5 a 7 minutos; el secado real es de 15 a 20 minutos. Touch-dry or open time is 5 to 7 minutes; full drying time is 15 to 20 minutes.

Application Instructions

To ensure a good adhesion and to avoid blistering due to incomplete solvent evaporation, check the "tack"; meaning when it feels sticky at touch, but no adhesive remain glued to your skin.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all its warranties are void.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO

Contact Cement

525-23792-100



-
- ✓ If this adhesive has been at rest for a long time, it should be stirred before use.
 - ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.

HEALTH

- ✓ This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ Note: Its sale is prohibited to minors, its inhalation can produce harmful effects on health, cause habit and dependence.
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.