

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO AMARILLO

Yellow Contact Cement

525-23795-100



DESCRIPTION

Cemento de Contacto 23795-100 is a professional adhesive, special for the leather and furniture industry. Easy to apply.

USE

Due to its qualities, it can be used to adhere leather, rubber, vinyl, cardboard, formica, polyurethane foam and many other materials

Line Industrial/Professional Line

CARACTERÍSTICAS PROPERTIES

SPECIAL PROPERTIES,

Appearance	Yellow, amber liquid
------------	----------------------------

PHYSICAL PROPERTIES

DATA

Volume Solids (%)	13 - 19
Weight solids (%)	19 - 21
Weight per gallon (kg/gal)	3.05 - 3.30
Brookfield Viscosity (cPs)	1200 - 2000
Density (kg/l)	0.806 - 0.872
Touch-dry Time (min)	10 - 25 min

Full performance of this adhesive is at 7 days after application

CONTAINERS

AVAILABLE CONTAINERS

55-gallon drum (208 Lt.)

SURFACE PREPARATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO AMARILLO

Yellow Contact Cement

525-23795-100



CONDITION	INSTRUCTION
Surface preparation	Surfaces should be dry and free of grease, oil, dust, or any other contaminants.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 525-23795-100, PEGAFORTE 100% CEMENTO DE CONTACTO AMARILLO		Ready to use, do not dilute

PRODUCT APPLICATION

APPLICATION TOOL

Brush Putty Knife Toothed Trowel Roller

Tools

Once the surfaces are prepared, it can be applied with brush, brush, spatula, toothed trowel or roller

Application Instructions

Apply the product on both sides.

After touch-checking the solvents evaporation, join firmly both parts in the desired position, apply pressure and let dry.

Temperature conditions, drafts, ambient humidity and thickness of the application affect open time of the adhesive.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ It should be used before the expiration date indicated on the packaging label. After that date, all its warranties are void.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PEGAFORTE CEMENTO DE CONTACTO AMARILLO

Yellow Contact Cement

525-23795-100



-
- ✓ Any change in environmental conditions at application can have a significant impact on its open time and drying time.
 - ✓ If this adhesive has been at rest for a long time, it should be stirred before use.

HEALTH

- ✓ A strong odor at application area is an indication of insufficient aeration
This a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ Not for sale to minors, inhalation may cause harmful health effects, and cause dependence habit.
- ✓ Si necesita disponer de los envases vacíos de nuestros productos en Costa Rica, acuda a su tienda Sur Color o a nuestro complejo industrial en La Uruca, San José. If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.