

# TECHNICAL INFORMATION

## KLEAR CERA ABRILLANTADORA EN PASTA

Glossy Car Wax

529-35300-102



### DESCRIPTION

**Cera Abrillantadora en Pasta Klear** is a car wax that gives the vehicle body an optimal protection against UV rays and inclement weather, leaving a clean and glossy surface. Made from solid-base high-performance waxes and polymers.

### USE

Use it for automotive finish maintenance. Ideal for frequent use and ease of application. Its paste form has an excellent yield and performance. Applied with hand tools, such as sponges, microfiber cloths and others.

**Structure** Car rims, painted body parts, spotlights, painted plastics

**Line** Domestic Line, Industrial / Professional Line

### FEATURES

#### PHYSICAL PROPERTIES

#### DATA

Appearance

Paste

### PRESENTATION

#### AVAILABLE CONTAINERS

11.5 oz can (340 ml)

1 gallon can (3,785 Lt)

Also available in liquid form.

### SURFACE PREPARATION

#### CONDITION

#### INSTRUCTION

**Freshly washed vehicle**

Car should be recently washed, dry and preferably in the shade.

### PRODUCT PREPARATION

#### COMPONENT

#### MIX RATIO

#### MIXING INSTRUCTIONS

Product: 529-35300-102, KLEAR CERA ABRILLANTADORA EN PASTA

**100 %**

Ready to use. Do not require dilution.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Aug  
1 2017



# TECHNICAL INFORMATION

## KLEAR CERA ABRILLANTADORA EN PASTA

Glossy Car Wax

529-35300-102



### PRODUCT APPLICATION

#### Application Instruction

Apply with hand tools, such as sponges, microfiber cloths, or others.

**Apply just 1 layer.**

This wax is applied in circular movements.

It should be applied in one part at a time and removed before it dries.

After application, run a second towel or dry sponge to enhance gloss.

For dust repellency, after wax, apply **Abrillantador Anti Estático 35425-330**.

### OBSERVATIONS

- ✓ If you need more information, check our web site <https://www.gruposur.com/asistencia/>  
Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or expose it to rain.  
Do not refrigerate this product

### HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Aug  
1 2017

