

DESCRIPTION

Klear Ceramic Wax helps protect paint and other exterior parts of vehicles, generating a water-proofing coat that repels water droplets and helps the car's body to remain clean for longer. Easy to apply and fast drying. Note: It should be used about once a month.

USE

This product is applied after washing and polishing the vehicle, protecting it from external agents and preventing it from deteriorating over time. In this way, it provides the vehicle body with a gloss enhancement.

Structure	Car Rims, Painted Bodywork or plastic, headlights
------------------	---

Line	Domestic Line, Industrial/Professional Line
-------------	---

PROPERTIES

SPECIAL PROPERTIES

DATA

Appearance	Liquid
------------	--------

CONTAINERS AND COLORS

AVAILABLE CONTAINERS

29.4 Fl. Oz (870 ml) plastic spray bottle

SURFACE PREPARATION

CONDITION

INSTRUCTION

Recently washed vehicle:	The vehicle must be recently washed, dry and preferably in the shade.
--------------------------	---

PRODUCT PREPARATION

COMPONENT

MIXING RATIO

MIXING INSTRUCTIONS

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLEAR CERAMIC WAX

529-35315-900



Product: 529-35315-900, KLEAR CERAMIC 100% WAX

Ready to use, do not dilute. Stir well before use

PRODUCT APPLICATION

Number of layers and thickness

1 coat

A second coat can be applied if necessary.

Application Instructions

Spray on a microfiber cloth, apply exerting mild pressure in circular movements.

Klear Ceramic Wax must be applied by parts, eliminating the excesses generated at application with a dry cloth.

This product is designed to be applied in one coat.

If you overapplied it, wipe off excess with a dry towel.

Repita el proceso de ser necesario. Repeat the process if necessary.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ Apply this product in the shade, allow it to dry completely before using the vehicle or exposing it to rain.
- ✓ Do not refrigerate it.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.