

# TECHNICAL INFORMATION

## KLEAR CERA PULIDORA

Polishing Car Wax

529-35350-330



### DESCRIPTION

**Cera Pulidora en Pasta** helps to remove weather stains and small streaks on the paint, while providing the vehicle body with an excellent protective glossy layer.

### USE

Use it to restore the gloss of a car's body, when its paint has already lost its original shine.

**Structure** Car rims, painted body parts, spotlights, painted plastics

**Line** Domestic Line, Industrial / Professional Line

### FEATURES

#### PHYSICAL PROPERTIES

#### DATA

Appearance

Paste

### PRESENTATION

#### AVAILABLE CONTAINERS

11.5 oz can (340 ML.)

### PRODUCT PREPARATION

#### COMPONENT

#### MIX RATIO

#### MIXING INSTRUCTIONS

Product: 529-35350-330, KLEAR CERA PULIDORA

**100 %**

Ready to use. Do not require dilution.

### PRODUCT APPLICATION

#### Application Instruction

Apply with hand tools, such as sponges, microfiber cloths, or others.

**Apply just 1 layer.**

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Jun  
26 2017



# TECHNICAL INFORMATION

## KLEAR CERA PULIDORA

Polishing Car Wax

529-35350-330



It should be applied in one part at a time, in circular movements, and removed before it dries.

After application, run a second towel or dry sponge to enhance gloss.

For dust repellency, after wax, apply **Abrillantador Anti Estático 35425-330**.

### OBSERVATIONS

- ✓ If you need more information, check our web site <https://www.gruposur.com/asistencia/>
  - Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or expose it to rain.
  - Do not refrigerate this product

### HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.1 del: Jun  
26 2017

