

TECHNICAL INFORMATION

KLEAR RESTAURADOR DE NEUMÁTICOS Y PIEZAS NEGRAS

529-35400-900



DESCRIPTION

KLEAR RESTAURADOR DE NEUMÁTICOS Y PIEZAS NEGRAS is a restorator for tires and black automotive parts with a high concentration of rubber protective surfactants and high water repellency. It does not contain solvents that can dry or damage automotive tires (rubber wheels) and black parts (unpainted molding).

USE

KLEAR RESTAURADOR DE NEUMÁTICOS Y PIEZAS NEGRAS is used to moisturize, restore and beautify the surface of black tires and parts, maintaining their flexibility and giving the surface a deep satin appearance, in every type of automotive vehicles. Ready-to-use product.

STRUCTURE Tires (Rubber automotive Wheels)

Line Domestic Line, Industrial/Professional Line

PROPERTIES

PHYSICAL PROPERTIES

DATA

Appearance:	Liquid
Mixture Color	Beige
Aroma	Fresh
Density	0.99 - 1.04 g/mL

CONTAINERS

AVAILABLE CONTAINERS

(exclusively for sale in KIT FOR BIKES)

240 ml plastic container

500 ml plastic container

870 ml plastic container

1 gallon plastic can (3.785 Lt.)

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLEAR RESTAURADOR DE NEUMÁTICOS Y PIEZAS NEGRAS

529-35400-900



5-gallon bucket (18.925 Lt.)

SURFACE PREPARATION

CONDITION	INSTRUCTION
Washing the tire:	Before applying, wash the tire to remove any dirt.

PRODUCT APPLICATION

Application conditions

Due to its high concentration, use only the amount necessary to give a satin appearance to the side surface of the tire and black parts (unpainted moldings).

Application instructions

Shake well before use: Pour over an applicator, avoiding splashing on other surfaces of the car. Using the same applicator, apply product to required surfaces.

If you applied excess product, wipe the excess with a dry towel.

NOTICE:

- ✓ If you need other information, visit our website at <https://www.gruposur.com/asistencia/>
- ✓ Store this product in its original container between 20°C and 30°C, in a dry, ventilated place, out of the reach of children.
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or exposing it to rain.

HEALTH

- ✓ If you need to dispose of empty packages of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.