

# TECHNICAL INFORMATION

## KLEAR ABRILLANTADOR ANTIESTÁTICO

### Anti-Static Shine

529-35425-330



#### DESCRIPTION

KLEAR Abrillantador Antiestático is a novel automotive product that contains lubricants, anticorrosive and antistatic agents. It leaves a glossy, high-protective finish that repels dust and dirt, so it prevents mild contamination.

#### USE

Used to repel dust on automotive paint, glass, plexiglass, gelcoat and painted fiberglass.

Line Domestic/ Industrial / Professional Line

#### FEATURES

#### PHYSICAL PROPERTIES

#### DATA

Appearance

Liquid

#### PRESENTATION

#### AVAILABLE CONTAINERS

1-gallon plastic container

#### SURFACE PREPARATION

#### CONDITION

#### INSTRUCTION

**Recently washed car** Car should be freshly washed, dry and, if possible, in the shadows.

#### PRODUCT PREPARATION

#### COMPONENT

#### MIXING RATIO

Product: 529-35425-330, KLEAR ABRILLANTADOR ANTIESTÁTICO 100%

#### PRODUCT APPLICATION

#### Application Instruction

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## KLEAR ABRILLANTADOR ANTIESTÁTICO

### Anti-Static Shine

529-35425-330



---

Spray the product at some 4 – 6 inches away from the surface and spread it with a microfiber towel or dry sponge. After the application, pass a second towel or dry sponge to enhance gloss. If you over-applied product, wipe off the leftover with a dry towel.

---

#### OBSERVATIONS

- ✓ If you need more information, check our web site <https://www.gruposur.com/asistencia/>
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or expose it to rain.  
Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Do not refrigerate this product

#### HEALTH

- ✓ Do not spray direct on plants, eyes, mouth or nose of humans or animals.

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

---

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.