

TECHNICAL INFORMATION

KLEAR REFRIGERANTE COOLANT

529-35650-622



DESCRIPTION

Klear Refrigerante Coolant is a ready to use coolant/antifreeze, offering protection to engine and cooling system against corrosion and formation of deposits for longer periods (Extended Life). It does not require to be diluted with water. Its state-of-the-art organic technology (OAT) formula protects all metals and alloys of cooling systems of gasoline internal combustion engines, without needing any complementary additives. This coolant helps keep units operating within their optimum temperature range and without evaporative loss.

USE

Klear Coolant is recommended for use undiluted in cooling systems of gasoline internal combustion engines. Meets specifications of ASTM D 3306 (Automobile and Light-Duty Service)

Structure	Gasoline engines
Line	Industrial/Professional Line

FEATURES

PHYSICAL PROPERTIES	DATA
Appearance	Líquid
Color	Phosphorescent green
pH	8 - 10
Density	1.00 - 1.05 Kg/L
Boiling Point	104 - 108°C
Biodegradability	YES (OECD 301F)

PRESENTATION

AVAILABLE CONTAINERS

4 liter plastic can

PRODUCT PREPARATION

COMPONENT	MIX RATIO	MIXING INSTRUCTIONS
Product: 529-35650-622, KLEAR REFRIGERANTE COOLANT		Ready to use. Do not add water. Do not mix with other coolants.

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLEAR REFRIGERANTE COOLANT

529-35650-622



Application Instruction

Check your vehicle owners' manual for the procedure to follow.

Drain the contents of the vehicle's cooling system (radiator and reserve tank).

Rinse cooling system with clean water, until water comes out completely clean.

Close the system drain and fill it with KLEAR REFRIGERANTE Coolant; close the radiator, fill the reserve tank, start the vehicle and bring it to normal operating temperature.

Turn off the engine, let it cool, open the reserve tank lid and refill if necessary.

Wash spilled product residues with soap and water.

Dispose of discarded coolant liquid according to local environmental regulations.

We suggest to replace your vehicle' coolant liquid once a year or as recommended by its manufacturer

OBSERVATIONS

- ✓ If you need more information, check our web site <https://www.gruposur.com/asistencia/>
- ✓ Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Do not refrigerate this product

SALUD

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.