



Automotive Degreaser

529-35770-900

DESCRIPTION

Klear Desengrasante Automotriz is an unscented, water soluble cleaner containing surfactants and emulsifying solvents of high cleaning power; effectively remove grease, oil, waxes and other residues deposited on different surfaces, even if they are difficult to reach.

USE

Use it on worktables, underbody car parts, bodies, external walls of diesel and gasoline engines, suspension parts and any non-porous surface made of stainless steel, aluminum or other substrates where excess grease is required to be removed. It can be used in professional environments, such as mechanical shops or lube centers.

Structure Equipment, Industrial, Car body, Engines

Line Domestic Line, Industrial / Professional Line

FEATURES

PHYSICAL PROPERTIES	DATA	
Appearance	Liquid	
Color	Yellowish	Color de
Aroma	Odorless	Aroma
pH	9 - 11	Valor de
Density (kg/Lt)	0.95 - 1.05	Densida

PRESENTATION

AVAILABLE CONTAINERS

0.23 gallon (0,870 Lt.) **OJO (1/4 de galón equivale a 0.946 l)**

1 gallon (3.785 Lt.)

5-gallon can (18.925 Lt.)

1 gallon can (3,785 Lt.)

55-gallon drum (208.175 Lt)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLEAR DESENGRASANTE AUTOMOTRIZ



Automotive Degreaser

529-35770-900

PRODUCT PREPARATION

COMPONENT	MIX RATIO	MIXING INSTRUCTIONS
Product: 529-35770-900, KLEAR DESENGRASANTE AUTOMOTRIZ	4:1	For light cleaning jobs: dilute four parts of this product with one part of tap water. For heavy-duty cleaning it can be used undiluted.

PRODUCT APPLICATION

Application Instruction

It can be applied with brush, spray or air compressor.

Apply the product over the contaminated areas generously (preferably when surface is at room temperature).

Leave it on between 3 to 5 minutes for a better performance.

Rinse with clean water.

If necessary, repeat the process until leaving the surface completely free of contaminants.

On hot surfaces, make sure that these do not exceed 80°C, considering that performance can be affected by forced evaporation.

OBSERVATIONS

- ✓ If you need more information, check our web site <https://www.gruposur.com/asistencia/>
Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or expose it to rain.
Do not refrigerate this product

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.