

TECHNICAL INFORMATION

KLEAR PROTECTOR PARA TELAS

529-35850-900



DESCRIPTION

KLEAR PROTECTOR PARA TELAS is a fabric protector that waterproofs and protects fabric upholstery by making it repellent to liquids and spills, thus eliminating the main cause of deterioration and discoloration. As it does not form a visible film on the fabric; once applied and dry, its protective effects are imperceptible to the eye or touch. Helps keep fabric clean longer.

USE

Use KLEAR PROTECTOR PARA TELAS only on new or freshly washed fabrics of fine and micro fine points upholstery to maintain its original condition. Ready-to-use product.

STRUCTURE

Upholstery

Line

Domestic Line, Industrial/Professional Line

PROPERTIES

PHYSICAL PROPERTIES

DATA

Appearance:

Liquid

Density

0.73 - 0.76 g/ml

CONTAINERS

AVAILABLE CONTAINERS

240 mL plastic spray bottle

5-gallon bucket (18.925 Lt.)

SURFACE PREPARATION

CONDITION

INSTRUCTION

Wash upholstery:

Before applying this product, wash upholstery to remove dirt or grease, as the presence of contaminants will not allow the product to penetrate, nullifying its protective effect.

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

KLEAR PROTECTOR PARA TELAS

529-35850-900



Application conditions

Spray product only on clean, dry surfaces.

Drying time

The product is dry-to-touch in 20 minutes and reaches its maximum protective effect 2 hours after drying.

Application instructions

Spray the product 10 - 15 centimeters from the surface and disperse with a microfiber towel or dry sponge.

Let this liquid to be absorbed by the first layer of the fabric.

After 2 hours, apply a second layer to completely seal the surface. If you want to reinforce the surface, a third layer can be applied without any problem.

Final Instructions

Repeat the application of this product every 6 to 8 weeks, after contact with contaminants or after a spill has been cleaned up.

Notes

This product does not remove existing stains on the fabric.

NOTICE:

- ✓ If you need other information, visit our website at <https://www.gruposur.com/asistencia/>
- ✓ Store this product in its original container between 20 °C and 30 °C, in a dry, ventilated place, out of the reach of children.
- ✓ Apply this product in the shade, let it dry completely before using the vehicle or exposing it to rain.
- ✓ Refrigeration of the contents of this container is not recommended

HEALTH

- ✓ If you need to dispose of empty packages of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose.
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUÍMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUÍMICA has made reasonable efforts to ensure the accuracy of the information provided herein, but assumes no liability for any errors, omissions or inaccuracies thereof. If there is any inconsistency between different language issues of this document, Spanish version will prevail.