

# TECHNICAL INFORMATION

## REPELENTE HIDROFÓBICO

### Water Repellent

529-36425-330



#### DESCRIPTION

Water and dust repellent, protects against contamination left by sea breeze and helps to keep boats cleaner for longer periods, leaving a nice, glossy protecting coat. Hi-tech product, containing lubricants, anti-rust, anti-static and hydrophobic ingredients.

#### USE

Use it to repel water and dust from smooth surfaces, leaving a glossy, protective finish. Apply on plexiglass, gelcoat, fiberglass or other painted materials, metals, varnished wood, acrylics and glass

**Structure** Boats, windows, wooden structures, leather, vinyl, painted or unpainted plastics, upholstery, glass

**Line** Domestic Line, Industrial/Professional

#### PROPERTIES

##### PHYSICAL PROPERTIES

##### DATA

Form

Liquid

Color

Pink

Density

0.95 - 1.0 g/ml

Viscosity

14 - 16 s (Zahn Cup #2)

#### CONTAINERS

##### AVAILABLE CONTAINERS

870 ml. Plastic spray (29.4 Fl. Oz.)

#### PRODUCT APPLICATION

#### APPLICATION INSTRUCTIONS

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## REPELENTE HIDROFÓBICO

### Water Repellent

529-36425-330



---

Boat should be clean, preferably freshly washed or even waxed. Spray this product generously at some 4 to 6 inches away from the surface and spread with a clean and dry microfiber cloth in linear movements, not in a circle.

Do not let the product dry out without spreading. After finishing this application, give it another pass, this time with a clean and dry cloth to enhance gloss.

Work in a cool, shady place, not under direct sunlight. It can be done also in the early hours of the morning or in late afternoon, when sun is not so high.

---

#### NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, between 20 and 30°C
- ✓ Do not refrigerate it.

#### HEALTH

- ✓ Do not spray directly on plants, nor over the eyes, mouth or nose of humans or animals.
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose
- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

---

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.