

TECHNICAL INFORMATION

DESOXIDANTE

DEOXIDANT



539-00318-900

DESCRIPTION

Deoxidant acid solution that allows to condition oxidized ferrous surfaces, leaving them free of rust, ready to apply an anticorrosive system.

USE

Specially formulated to condition ferrous surfaces.

CHARACTERISTICS

PHYSICAL PROPERTY

DATA

Weight per Gallon (kg/gal)	4,15 - 4,25
Appearance	Transparent liquid
pH	< 3
Zahn Cup # 2 (s)	13 - 15
Odor	Typically acid

PRESENTATION

AVAILABLE PRESENTATIONS

1 gallon can (3.785 Lt.)

1 liter can

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product : 539-00318-900 DEOXIDANT	100 %	Ready to use. Do not dilute.

If surface has flake corrosion, these must be removed with tools. Moisten the surface with water, then apply Deoxidant 318-900 according to these instructions.

PRODUCT APPLICATION

Application Instructions

Moisten the surface to be deoxidized with clean water.
Apply this product with a brush, roller or tow and scrub well.
Leave on for 20 minutes, then rinse with plenty of clean water.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

DESOXIDANTE

DEOXIDANT



539-00318-900

In severe cases of corrosion, repeat the procedure.
Once the surface is dry, paint with a SUR anticorrosive system.

OBSERVATIONS

- ✓ Do not apply under direct sunlight, to avoid accelerated drying. Do not apply over hot surfaces or directly exposed to the sun, because it will evaporate very fast and this will cut the time needed for this product to perform properly.
If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com

HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.
Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.