

TECHNICAL INFORMATION PVA CLEANING SOLUTION



SOLUCIÓN LIMPIADORA DE PVA PARA RODILLOS

539-00329-900

DESCRIPTION

PVA CLEANING SOLUTION is an industrial product designed to remove PVA adhesive dry residue from dual arch corrugating machinery surfaces and from metal or nitrile rubber rollers, without damaging the equipment. Water soluble product.

USE

Use to remove PVA adhesive residues from different parts of the application equipment, as rollers, nozzles and other.

Does not harm equipment parts or materials, as nitrile rubber or similar.

Product line

Professional/industrial Line

CHARACTERISTICS

ASSESSMENT

Appearance

Colorless liquid.

PHYSICAL PROPERTY

DATA

Density (kg/l)

0.94 a 0.96

pH

7 - 9

PRESENTATION

AVAILABLE PRESENTATIONS

5 Gallon plastic bucket (18.925 lt)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over the conditions, tools, the skills of the applicator, or over the selection, preparation or compatibility of the products used; therefore can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.



539-00329-900

Application Instructions

Stir before use.
Clean surface from dust and dirt.
Spray product direct on the surface to clean, wait some 5 - 10 minutes until dry, adhered residue starts to soften.
If necessary, help to remove residue with a plastic spatula.
Wash with water or damp cloth to remove loosen residues.
Repeat until surface is clean, free of residue.
This product has flammable ingredients, keep away from flames or heat sources.
After use, keep container properly closed to avoid evaporation.

OBSERVATIONS

- ✓ If you need more information, one of our technicians will assist you. Call 800-SUR-2000 or email us at customerservice@gruposur.com
- ✓ Store the product in its closed, sealed original container between 20°C and 30°C, in a dry and ventilated place, far from sunlight, out of the reach of children.
- ✓ Manage your inventory, use first those containers with earlier expiration date, as indicated by its label.

HEALTH

- ✓ Application personnel should use appropriate personal protective equipment, including safety gloves, goggles and activated charcoal respirator, as detailed in its safety data sheet (MSDS), available at www.gruposur.com
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over the conditions, tools, the skills of the applicator, or over the selection, preparation or compatibility of the products used; therefore can only guarantee this product's quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it.