

TECHNICAL INFORMATION

INKKER LITOKLEAN

Offset Ink Cleaner

539-33165-100



DESCRIPTION

INKKER LITOKLEAN 539-33165-100 is an offset ink cleaner for printing equipment. Remove stains and traces of recent or dried ink on rollers and blankets.

USE

This product can be applied manually or in the automatic cleaning cycle of the printing press. Manually, it can be used pure, undiluted, or diluted in water (3 parts of product in 1 part of water). For automatic machine cleaning, the dilution is adjusted by the printing press washing program or instructions. For more details see "Application Instructions" below.

Structure Industrial Equipment, Industrial

Line Industrial/Professional Line

PROPERTIES

SPECIAL PROPERTIES

Appearance	Yellowish liquid
------------	------------------

PHYSICAL PROPERTIES

DATA

pH	7.0 - 8.0
Zahn Cup #4 Viscosity (s)	5 - 7
Density (kg/l)	0.82 - 0.85

CONTAINERS

AVAILABLE CONTAINERS

1 gallon can (3.785 Lt.)
5-gallon bucket (18.925 Lt.)
55-gallon drum (208 Lt.)

PRODUCT PREPARATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



TECHNICAL INFORMATION

INKKER LITOKLEAN

Offset Ink Cleaner

539-33165-100



COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 539-33165-100, INKKER LITOKLEAN	3:1	For manual use, it can be used pure, or diluted in water (3 parts of product and 1 part of water).

APLICACIÓN DEL PRODUCTO

APPLICATION TOOL

Brush Putty Knife Spray gun (gravity or Roller suction fed)

Application Instructions

For manual cleaning: Spray a wick or cloth that leaves no lint or residue and clean ink-stained area of the roller or blanket.

Once you remove the ink stains the cloth, let the surface dry.

After use, keep the container tightly closed to prevent evaporation.

For automatic cleaning: Use the printing press automated cleaning program. The dilution is automatically prepared by the equipment according to its cleaning cycle.

NOTICE

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ Do not mix with other cleansing products.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose
- ✓ This a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Versión 1.0 del: Feb 2/11/2021
11 2021 3:02PM

