

TECHNICAL INFORMATION

BECC COLOR PASTE 570

555-00570-000



DESCRIPTION

BECC COLOR PASTE 570 is made from polyester resin and it's used to color parts made from reinforced plastic or synthetic marble.

USE

BECC COLOR PASTE 570 is used for the manufacture of parts reinforced with fiberglass and synthetic marble. Do not use in proportions over 10% of weight of resin or gelcoat.

Product Line Industrial/Professional Line

CHARACTERISTICS

PHYSICAL PROPERTIES

DATA

| | | |
|----------------------------|------------------|-------------|
| Volume Solids (%) | | 99 - 100 |
| Product Useful life | | 12 months |
| Weight per Gallon (kg/gal) | White 000 | 6.70 – 7.20 |
| | Yellow 100 | 4.70 – 4.90 |
| | 300 Bright Red | 4.70 – 5.10 |
| | 500 Intense Blue | 3.96 – 4.15 |
| | Green 600 | 4.20 – 4.40 |
| | Black 700 | 4.60 – 4.80 |

CONTAINERS

AVALLABLE CONTAINERS

¼ gallon can

AVAILABLE COLORS

White 000
Yellow 100
Bright Red 300
Intense Blue 500
Green 600
Black 700

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface: Area to be repaired and its surroundings should be completely clean, dry and free of loose material.
Sand the repair area with #180 or #22 grits.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

BECC COLOR PASTE 570

555-00570-000



PRODUCT PREPARATION

| COMPONENT | MIXTURE RATIO | MIXING INSTRUCTIONS |
|--|---------------|---|
| Product: 555-00570-000, BECC COLOR PASTE 570 | 100% | Mix well with resin or gelcoat. Do not use in proportions over 10% of weight of resin or gelcoat |

PRODUCT APPLICATION

APPLICATION TOOL

Manual use.

OBSERVATIONS

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
Keep out of reach of children.

Container must be kept tightly closed in a ventilated place, between 20 and 30°C to avoid loss of its properties.

HEALTH

- ✓ This is a professional/industrial product and it should be applied by properly trained personnel, wearing appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.