

TECHNICAL INFORMATION

BECC FILM PVAL



555-00622-900

DESCRIPTION

BECC FILM PVAL is a protective film for molds used to make fiber parts, so the fiber compound does not adhere to it. It creates a uniform film with good drying speed. Excellent balance between performance and price.

USE

BECC FILM PVAL is used as a protective film on mold surfaces, to prevent the adhesion of fiber materials on the mold walls.

Product line Professional/Industrial Line

CHARACTERISTICS

PHYSICAL PROPERTY

DATA

Weight solids (%)	10 - 12
Weight per Gallon, Component A (kg/gal)	3.50 - 3.70

CONTAINERS

AVAILABLE CONTAINERS

555-00622-900: 0.908 kg in ¼ gallon plastiv container

AVAILABLE COLORS

900 Neutral

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product; 555-00622-900 BECC FILM PVAL	100 parts	Ready to use, does not need dilution

PRODUCT APPLICATION

IT CAN BE APPLIED WITH

Sponge



Spray gun (Gravity or suction feed)

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 2.0 of: Sep
2021 3:46PM



TECHNICAL INFORMATION

BECC FILM PVAL



555-00622-900

Application conditions

Application should be carried out evenly, on the previously waxed mold and with the appropriate gloss.

OBSERVATIONS

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Keep container tightly closed in a ventilated place, between 20 and 30°C, out of reach of children.
- ✓ Container must be kept tightly closed to avoid loss of its properties.

HEALTH

- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.
- ✓ This product is for professional/industrial use only and must be applied by trained personnel, using the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.



Version 2.0 of: Sep
2021 3:46PM

