

TECHNICAL INFORMATION

BECCWAX



555-14004-000

DESCRIPTION

BECCWAX is a release wax in solid form, for high temperature and room temperature. It contains synthetic waxes and additives that produce highly effective plastic releases.

USE

BECCWAX is excellent for effective release of fiberglass-reinforced plastic or cultivated marble parts. It ensures fast and perfect releases without sticking nor leaving residues in the transfer.

Product line Professional/Industrial Line

CHARACTERISTICS

PHYSICAL PROPERTY

DATA

Odor	Lightweight Aliphatic Solvent
Appearance	Slightly yellowish paste wax
Specific density	0.79 – 0.83

PRESENTATION

AVAILABLE PRESENTATIONS

Product: 555-14004-000, BECCWAX

700 grams metallic can (approx. 25 Oz.)

SURFACE PREPARATION

CONDITIONS

INSTRUCTIONS

Surface Preparation

Surface should be dry and free of dust or any other contaminants

PRODUCT APPLICATION

IT CAN BE APPLIED WITH

Manual Use

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

BECCWAX



555-14004-000

Application Instructions

Apply by parts, in circular motions.

Do not wait for it to dry, easier to remove when wet.

After the application, pass a second towel or dry sponge to enhance gloss.

OBSERVATIONS

- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>
- ✓ Keep container tightly closed in a ventilated place, between 20 and 30 °C, out of reach of children.

HEALTH

- ✓ This product is for professional/industrial use only and must be applied by trained personnel, using the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.