

TECHNICAL INFORMATION

PASTA LISA PARA EXTERIORES

Exterior Wall Plaster



596-41200-000

DESCRIPTION

Pasta Lisa para Exteriores is a wall plaster made from an optimal mixture of fillers and additives that make it ideal for creating smooth surfaces with high weather resistance, while allowing good sandability. It should be coated as soon as possible.

USE

It can be applied over concrete or masonry walls.

Structure	Walls, fascia boards.
Exterior/Interior	Outdoor, Roofed Outdoors
Surface	Concrete, plastered walls, lightweight boards.

CHARACTERISTICS

SPECIAL PROPERTIES

Appearance **WHITE**

PHYSICAL PROPERTY

DATA

Brookfield Viscosity (cPs)	400 000 - 500 000
Theoretical yield (kg/m ²)	1.0 kg/m ²

Definition of theoretical yield: Maximum surface that a paint can cover under ideal conditions. Practical performance varies depending on type of surface, used tool, applicator experience and other factors. 1 mil = 0.0254 mm.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PASTA LISA PARA EXTERIORES

Exterior Wall Plaster

596-41200-000



PRESENTATIONS

AVAILABLE CONTAINERS

- 18 kg cardboard box
- 17 kg plastic container
- 30 kg plastic container (5-gallon bucket)

AVAILABLE COLORS

SURFACE PREPARATION

CONDITION

INSTRUCTION

Surface Cleaning

Before applying, remove any dirt, such as dust, grease, or other contaminants, as they can affect the adhesion or performance of the finish.

Remove loose or peeling old paint film with the appropriate tools, and smooth uneven spots left by old coat of paint.

Concrete

All new surfaces must be fully cured, usually about 30 days (setting time), dry and clean.

Over the cured surface, apply this plaster.

Apply one layer of **SELLADOR BLANCO 522-000** (White Sealant) and coat with your selected SUR finish.

Mildew, Mold

Apply **SOLUCIÓN FUNGICIDA 334-900** (Antifungal Solution), let on the surface for some 20 minutes. Rinse with enough clean water and scrub the area.

Where washing is not possible, apply **NIT CLINICAL DISINFECTANT CLEANER 4 33260-600**, scrub with a microfiber cloth, apply again and let dry on the surface.

After cleaning, be sure the surface is thoroughly dry before applying this plaster and a coat of **SELLADOR BLANCO** (white

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PASTA LISA PARA EXTERIORES

Exterior Wall Plaster

596-41200-000



sealer) 522-000 diluted with a 20 to 25 % of tap water to improve impregnation and top with your SUR selected finish.

Small cracks and cracks in masonry or concrete

Small Cracks (0.6 mm a 2 mm): Repair with **PEGA-PATCH** Elastomeric Putty 231-000 and cover with this finish.

Cracks (2 mm a 20 mm): Use 550 **ETIBOND CONCRET** and immediately, "fresh on fresh", apply **MORTERO DE REPARACIÓN MR-520** (repair mortar).

Let the mortar cure and dry for at least 15 days before applying this plaster.

Once dry, sanded and dusted, coat with of **SELLADOR BLANCO 522-000** (white sealer) and your selected SUR finish.

Important: For cracks wider than described, refer to the Virtual Assistant or request an assessment from our Technical Service.

Moisture, damp on concrete or masonry walls

Do not use this plaster over surfaces with present or past moisture problems.

Mild concrete dusting

Do not apply this product. In doubt, ask for an evaluation from our Technical Service.

PRODUCT PREPARATION

COMPONENT	MIXING RATIO	MIXING INSTRUCTIONS
Product: 596-41200-000, PASTA LISA PARA EXTERIORES	100%	

PRODUCT APPLICATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PASTA LISA PARA EXTERIORES

Exterior Wall Plaster

596-41200-000



IT CAN BE APPLIED WITH

Stainless steel Trowel

Application conditions

Do not apply on hot surfaces or directly exposed to sunrays, paint will evaporate too soon, and this will affect leveling, adhesion and durability.

Don't apply when humidity is over 85%, or in a rainy day.

Number of layers and thickness

Number of Coats	2 or more
-----------------	-----------

Drying times

Dry-to-Touch Time	30 - 45 minutes
-------------------	-----------------

Re-coat time	4 - 5 hours
--------------	-------------

Time-to-sand	6 hours at least
--------------	------------------

Time to apply sealer	24 hours
----------------------	----------

Drying times listed are under ideal conditions (Between 22-28°C temperature and 50 - 80% relative humidity). These times are dependent on temperature, moisture, film thickness and dilution.

OBSERVATIONS

- ✓ Keep container tightly closed in a ventilated place, between 20 and 30°C, out of reach of children.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

TECHNICAL INFORMATION

PASTA LISA PARA EXTERIORES

Exterior Wall Plaster



596-41200-000

-
- ✓ If you'll use more than one container, mix them in advance to correct any color differences.
 - ✓ Do not wash a painted surface with abrasive detergents, it is better to use liquid detergent with enough water and a soft sponge.
 - ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>

HEALTH

- ✓ User may need to wear the appropriate Personal Protective Equipment, which is detailed in the respective Safety Data Sheet (MSDS), available at <http://www.gruposur.com>

If you need to dispose of empty containers of our products in Costa Rica, contact your SUR Color paint store or our industrial compound in La Uruca, San Jose.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.