

# TECHNICAL INFORMATION

## DURABLE PASTA LISA PARA INTERIORES

Finishing Plaster

596-59915-000



### DESCRIPTION

DURABLE PASTA LISA PARA INTERIORES is a finishing plaster made with the best raw materials and the strictest quality control, thus guaranteeing an exceptional finish. This product is easy to apply, allowing a variety of decorative relief techniques, or to leave a smooth and soft finish with unparalleled appearance. Odorless.

### USE

This product can be applied indoors on concrete, plasterboard, and wood surfaces.

**Structure** Walls

**Interior/Exterior** Indoors

**Surface** Concrete, Wood, plastered surfaces, Gypsum

### PROPERTIES

#### SPECIAL PROPERTIES

**Finish** Smooth texture

#### PHYSICAL PROPERTIES

#### DATA

Practical Yield

1.0 kg/m<sup>2</sup>

Brookfield Viscosity (cPs)

380.000 - 480.000

Definition of theoretical yield: Maximum surface that can be covered with a painting under ideal conditions. Practical yield varies depending on type of surface, used tool, applicator experience and other factors. 1 mil = 0.0254 mm.

### CONTAINERS and COLORS

#### AVAILABLE CONTAINERS

15 kilo bags

5-gallon bucket (18.925 Lt.)

#### AVAILABLE COLORS

White

### SURFACE PREPARATION

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## DURABLE PASTA LISA PARA INTERIORES

Finishing Plaster

596-59915-000



CONDITION	INSTRUCTION
<b>Mild concrete dusting</b>	Do not apply this product. In doubt, ask for an evaluation from our Technical Service.
<b>Moisture Problems</b>	Do not apply to surfaces that have or had moisture problems
<b>Surface Cleaning</b>	<p>Before applying, remove any dirt, such as dust, grease, or other contaminants, as they can affect the adhesion or performance of the finish.</p> <p>Remove loose or peeling old paint film with the appropriate tools, and smooth uneven spots left by old coat of paint.</p>
<b>Small cracks and cracks in masonry or concrete</b>	<p>Small Cracks (0.6 mm a 2 mm): Repair with SELLADOR HÍBRIDO or with MASILLA ELASTOMÉRICA PEGA PATCH 231-000. and cover with this finish.</p> <p>Cracks (3mm to 20mm): Use 550 ETIBOND CONCRET and immediately, "fresh on fresh", apply MORTERO DE REPARACIÓN MR-520 (repair mortar).</p> <p>Let the mortar cure and dry for at least 15 days before applying this plaster.</p> <p>Once dry, sanded and dusted, coat with of SELLADOR AQ 930 DURABLE (white sealer) and then apply this plaster.</p> <p>Important: For cracks wider than described, refer to the Virtual Assistant or request an assessment from our Technical Service.</p>
<b>Mildew, Mold</b>	<p>Apply SOLUCIÓN FUNGICIDA 334-900 (Antifungal Solution), let on the surface for some 20 minutes. Rinse with enough clean water and scrub the area.</p> <p>Where washing is not possible, apply NIT LIMPIADOR DE MOHO Y HONGOS 33305-600, scrub with a microfiber cloth, apply again and led dry on the surface.</p> <p>After cleaning, be sure the surface is thoroughly dry before applying this plaster and a coat of DURABLE SELLADOR AQ 930 and apply this plaster.</p>
<b>Gypsum board</b>	<p>Plaster the surface, sand, and thoroughly clean residual dust with a clean microfiber cloth.</p> <p>Apply 1 coat of DURABLE SELLADOR AQ 930 diluted with 20 to 25% water to improve surface infiltration, let dry and apply this plaster.</p>

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## DURABLE PASTA LISA PARA INTERIORES

Finishing Plaster

596-59915-000



### PRODUCT APPLICATION

#### Application conditions

Do not apply on hot surfaces or directly exposed to sunrays, paint will evaporate too soon, and this will affect leveling, adhesion and durability.

Do not apply this product when the relative humidity exceeds 85%, with rain or with certain threat that it will rain in a short time, as it would alter some characteristics of the application or the performance of the product.

#### Number of layers and thickness

Number of layers	At least 2
------------------	------------

#### Drying Times

Touch-Dry time	30 - 45 minutes
----------------	-----------------

Drying time between layers	4 - 5 hours
----------------------------	-------------

Drying time to sand	At least 6 hours
---------------------	------------------

Drying time before applying a sealer	24 hours
--------------------------------------	----------

Drying times listed are under ideal conditions (Between 22-28°C temperature and 50 - 80% ambient humidity). These times are dependent on temperature, moisture, film thickness and dilution.

#### Application instructions

Do not apply in thick coats. Apply next layer once the previous one dries. Respect drying times for each procedure.

Note: As every other acrylic plaster, this product should be coated by a sealer. In this case, by Durable Sellador AQ 930.

Is important that this sealer is diluted with 20% to 25% of clean water for a better permeating and consolidation of the surface.

### NOTICE

- ✓ Container must be kept out of reach of children, tightly closed in a ventilated place, away from sunlight or intense heat, between 20 and 30°C to avoid loss of its properties.
- ✓ If you'll use more than one container, mix them in advance to make up for any color differences.
- ✓ Do not wash a painted surface with abrasive detergents, it is better to use liquid detergent with water and soft sponge.

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.

# TECHNICAL INFORMATION

## DURABLE PASTA LISA PARA INTERIORES

Finishing Plaster

596-59915-000



- 
- ✓ If you need more information, check our website <https://www.gruposur.com/asistencia/>

### HEALTH

- ✓ The user of this product may need the appropriate Personal Protection Equipment (PPE), as described in its Safety data Sheet (MSDS), available at <http://www.gruposur.com>
- ✓ If you need to dispose of empty containers of our products in Costa Rica, contact your SUR store or our industrial compound in La Uruca, San Jose

---

These technical data were calculated under controlled laboratory conditions, but SUR QUIMICA has no control over conditions, tools, applicator skills, selection, preparation, or compatibility of products used; therefore, can only guarantee this product quality, its features and qualities' suitability, but is not responsible for the results obtained in conditions impossible to check once the job has been done. SUR QUIMICA has made reasonable efforts to ensure the accuracy of the information provided here, but assumes no responsibility for any error, omission, or inaccuracy in it. If there is any inconsistency between different language issues of this document, Spanish version will prevail.